



SPECIAL ISSUE

Kenya Gazette Supplement No. 87

1691

28th June, 2018

(Legislative Supplement No. 41)

LEGAL NOTICE NO. 134

THE CIVIL AVIATION ACT

(No. 21 of 2013)

THE CIVIL AVIATION (AERONAUTICAL CHARTS)
REGULATIONS, 2018



ARRANGEMENT OF REGULATIONS

PART I—PRELIMINARY PROVISIONS

1. Citation and commencement
2. Interpretation
3. Application
4. Availability

PART II—GENERAL SPECIFICATIONS

5. Operational requirements for charts
6. Titles
7. Miscellaneous information
8. Symbols
9. Units of measurement
10. Scale and projection
11. Date of validity of aeronautical information
12. Spelling of geographical names
13. Abbreviations
14. Political boundaries
15. Colours
16. Relief
17. Prohibited, restricted and danger areas
18. Air traffic services
19. Magnetic variation
20. Aeronautical data
21. Horizontal reference system
22. Vertical reference system

	
THE NATIONAL ASSEMBLY PAPERS LAID	
DATE: 10 SEP 2019	DAY: TUESDAY
TABLED BY:	MAJORITY LEADER
CLERK-AT THE TABLE:	

23. Temporal reference system
24. Charts to be published
25. Use of automation in aeronautical charting

PART III—AERODROME OBSTACLE CHART –
INTERNATIONAL CIVIL AVIATION ORGANIZATION
TYPE A (OPERATING LIMITATIONS)

26. Function
27. Availability
28. Units of measurement
29. Coverage and scale
30. Format
31. Identification
32. Magnetic variation
33. Obstacles
34. Take of flight path area
35. Declared Distances
36. Plan and profile views
37. Accuracy

PART IV—AERODROME OBSTACLE CHART –
INTERNATIONAL CIVIL AVIATION ORGANIZATION TYPE B

38. Function
39. Availability
40. Units of measurement
41. Coverage and scale
42. Format
43. Identification
44. Culture and topography
45. Magnetic variation
46. Aeronautical data
47. Accuracy

PART V—AERODROME TERRAIN AND OBSTACLE CHART –
INTERNATIONAL CIVIL AVIATION ORGANIZATION
(ELECTRONIC)

48. Function
49. Availability
50. Identification

51. Chart Coverage

- 52. General Specifications
- 53. Terrain Feature
- 54. Obstacle Features
- 55. Aerodrome Features
- 56. Radio Navigation aid features
- 57. Accuracy and resolution
- 58. Electronic functionality
- 59. Chart data product specifications

PART VI—PRECISION APPROACH TERRAIN CHART -
INTERNATIONAL CIVIL AVIATION ORGANIZATION

- 60. Function
- 61. Availability
- 62. Scale
- 63. Identification
- 64. Plan and profile information

PART VII—EN-ROUTE CHART - INTERNATIONAL CIVIL
AVIATION ORGANIZATION

- 65. Function
- 66. Availability
- 67. Coverage and Scale
- 68. Projection
- 69. Identification
- 70. Culture and topography
- 71. Magnetic variation
- 72. Bearings, tracks and radials
- 73. Aerodromes
- 74. Prohibited, restricted and danger areas
- 75. Air traffic services system
- 76. Supplementary information

PART VIII—AREA CHART- INTERNATIONAL CIVIL AVIATION
ORGANIZATION

- 77. Function
- 78. Availability
- 79. Coverage and Scale

80. Projection
81. Identification
82. Culture and topography
83. Magnetic variation
84. Bearings, tracks and radials
85. Aerodromes
86. Prohibited, restricted and danger areas
87. Area Minimum altitudes
88. Air traffic services system

PART IX—STANDARD DEPARTURE CHART – INSTRUMENT
(SID) - INTERNATIONAL CIVIL AVIATION ORGANIZATION

89. Function
90. Availability
91. Coverage and Scale
92. Projection
93. Identification
94. Culture and topography
95. Magnetic variation
96. Bearings, tracks and radials
97. Aerodromes
98. Prohibited, restricted and danger areas
99. Minimum sector altitude
100. Air traffic services system
101. Aeronautical database requirements

PART X—STANDARD ARRIVAL CHART –
INSTRUMENT (STAR) - INTERNATIONAL CIVIL
AVIATION ORGANIZATION

102. Function
103. Availability
104. Coverage and Scale
105. Projection
106. Identification
107. Culture and topography
108. Magnetic variation
109. Bearings, tracks and radials

110. Aerodromes

- 111. Prohibited, restricted and danger areas
- 112. Minimum sector altitude
- 113. Air traffic services system
- 114. Aeronautical database requirements

PART XI—INSTRUMENT APPROACH CHART -
INTERNATIONAL CIVIL AVIATION ORGANIZATION

- 115. Function
- 116. Availability
- 117. Coverage and Scale
- 118. Format
- 119. Projection
- 120. Identification
- 121. Culture and topography
- 122. Magnetic variation
- 123. Bearings, tracks and radials
- 124. Aerodromes
- 125. Obstacles
- 126. Prohibited, restricted and danger areas
- 127. Radio communication facilities and navigation aids
- 128. Minimum sector altitude or terminal arrival altitude
- 129. Portrayal of procedure tracks
- 130. Aerodrome operating minimum
- 131. Supplementary cartographic
- 132. Aeronautical database requirements

PART XII—VISUAL APPROACH CHART –
INTERNATIONAL CIVIL AVIATION ORGANIZATION

- 133. Function
- 134. Availability
- 135. Scale
- 136. Format
- 137. Projection
- 138. Identification
- 139. Culture and topography
- 140. Magnetic variation

- 141. Bearings, tracks and radials
- 142. Aerodromes
- 143. Obstacles
- 144. Prohibited, restricted and danger areas
- 145. Designated airspace
- 146. Visual approach information
- 147. Supplementary information

PART XIII—AERODROME/HELIPORT – INTERNATIONAL
CIVIL AVIATION ORGANIZATION

- 148. Function
- 149. Availability
- 150. Coverage and Scale
- 151. Identification
- 152. Magnetic variation
- 153. Aeronautical/heliport data

PART XIV—AERODROME GROUND MOVEMENT CHART –
INTERNATIONAL CIVIL AVIATION ORGANIZATION

- 154. Function
- 155. Availability
- 156. Coverage and Scale
- 157. Identification
- 158. Magnetic variation
- 159. Aerodrome data

PART XV—AIRCRAFT PARKING/DOCKING CHART –
INTERNATIONAL CIVIL AVIATION ORGANIZATION

- 160. Function
- 161. Availability
- 162. Coverage and Scale
- 163. Identification
- 164. Magnetic variation
- 165. Aerodrome data

PART XVI—WORLD AERONAUTICAL CHART -
INTERNATIONAL CIVIL AVIATION ORGANIZATION

1:1 000 000

- 166. Function
- 167. Availability
- 168. Scales
- 169. Format

170. Projection

- 171. Identification
- 172. Built up areas
- 173. Rail roads
- 174. Highway and Roads
- 175. Landmarks
- 176. Political Boundaries
- 177. Hydrology
- 178. Contours
- 179. Hypsometric tints
- 180. Spot Elevations
- 181. Incomplete or unreliable relief
- 182. Escarpments
- 183. Wooded areas
- 184. Date of topographic information
- 185. Magnetic variation
- 186. General
- 187. Aerodromes
- 188. Obstacles
- 189. Prohibited, restricted and danger areas
- 190. Air traffic services system
- 191. Radio navigation aids
- 192. Supplementary information

PART XVII—AERONAUTICAL CHART - INTERNATIONAL
CIVIL AVIATION ORGANIZATION 1:500 000

- 193. Function
- 194. Availability
- 195. Scales
- 196. Format
- 197. Projection
- 198. Identification
- 199. Built up areas
- 200. Rail roads
- 201. Highway and Roads

- 202. Landmarks
- 203. Political Boundaries
- 204. Hydrology
- 205. Contours
- 206. Hypsometric tints
- 207. Spot Elevations
- 208. Incomplete or unreliable relief
- 209. Escarpments
- 210. Wooded areas
- 211. Date of topographic information
- 212. Magnetic variation
- 213. General information
- 214. Aerodromes
- 215. Obstacles
- 216. Prohibited, restricted and danger areas
- 217. Air traffic services system
- 218. Radio navigation aids
- 219. Supplementary information

PART XVIII—AERONAUTICAL NAVIGATION CHART -
INTERNATIONAL CIVIL AVIATION ORGANIZATION
SMALL SCALE

- 220. Function
- 221. Availability
- 222. Coverage and Scale
- 223. Format
- 224. Projection
- 225. Built up areas
- 226. Rail roads
- 227. Highway and Roads
- 228. Political Boundaries
- 229. Hydrology
- 230. Contours
- 231. Hypsometric tints
- 232. Spot Elevations
- 233. Incomplete or unreliable relief

234. Date of topographic information

- 235. Colours
- 236. Magnetic variation
- 237. Aerodromes
- 238. Obstacles
- 239. Prohibited, restricted and danger areas
- 240. Air traffic services system

PART XIX—PLOTING CHART – INTERNATIONAL CIVIL AVIATION ORGANIZATION

- 241. Function
- 242. Availability
- 243. Coverage and Scale
- 244. Format
- 245. Projection
- 246. Identification
- 247. Culture and topography
- 248. Magnetic variation
- 249. Aeronautical data

PART XX—ELECTRONIC AERONAUTICAL CHART DISPLAY – INTERNATIONAL CIVIL AVIATION ORGANIZATION

- 250. Function
- 251. Information available for display
- 252. Display Categories
- 253. Display mode and generation of neighbouring area
- 254. Scale
- 255. Symbols
- 256. Display hardware
- 257. Provision and updating of data
- 258. Performance tests, malfunction alarms and indications
- 259. Back-up arrangements

PART XXI—AIR TRAFFIC CONTROL SURVEILLANCE MINIMUM ALTITUDE CHART – INTERNATIONAL CIVIL AVIATION ORGANIZATION

- 260. Function
- 261. Availability

- 262. Coverage and Scale
- 263. Projection
- 264. Identification
- 265. Culture and topography
- 266. Magnetic variation
- 267. Bearing, tracks and radials
- 268. Aerodromes
- 269. Prohibited, restricted and danger areas
- 270. Air traffic services system
- 271. Transition provisions.

SCHEDULES

FIRST SCHEDULE	Marginal layout
SECOND SCHEDULE	International Civil Aviation Organization Chart Symbols
THIRD SCHEDULE	Colour Guide
FOURTH SCHEDULE	Hypsometric Tint Guide
FIFTH SCHEDULE	Sheet Layout index for the World Aeronautical Chart – International Civil Aviation Organization 1:1,000,000
SIXTH SCHEDULE	Aeronautical data quality requirements

THE CIVIL AVIATION ACT

(No. 21 of 2013)

IN EXERCISE of the powers conferred by section 82 of the Civil Aviation Act, 2013, the Cabinet Secretary for Transport and Infrastructure makes the following Regulations—

THE CIVIL AVIATION (AERONAUTICAL CHARTS) REGULATIONS, 2018

PART I—PRELIMINARY

1. (1) These Regulations may be cited as the Civil Aviation (Aeronautical Charts) Regulations 2018. Citation.

2. In these Regulations, unless the context otherwise requires— Interpretation

“Aerodrome” means a defined area on land or water (including any buildings, installations and equipment) intended to be used either wholly or in part for the arrival, departure and surface movement of aircraft;

“Aerodrome elevation” means the elevation of the highest point of the landing area;

“Aerodrome operating minima” means the limits of usability of an aerodrome for—

- (a) take-off, expressed in terms of runway visual range or visibility and, if necessary, cloud conditions;
- (b) landing in precision approach and landing operations, expressed in terms of visibility or runway visual range and decision altitude/height as appropriate to the category of the operation;
- (c) landing in approach and landing operations with vertical guidance, expressed in terms of visibility and/or runway visual range and decision altitude/height; and
- (d) landing in non-precision approach and landing operations, expressed in terms of visibility and/or runway visual range, minimum descent altitude/height and, if necessary, cloud conditions;

“Aerodrome reference point” means the designated geographical location of an aerodrome;

“Aeronautical chart” means a representation of a portion of the Earth, its culture and relief, specifically designated to meet the requirements of air navigation;

“Aircraft stand” means a designated area on an apron intended to be used for parking an aircraft;

“Air defence identification zone” means a special designated airspace of defined dimensions within which aircraft are required to comply with special identification or reporting procedures additional to those related to the provision of air traffic services;

“Air traffic service” means a generic term meaning variously, flight information service, alerting service, air traffic advisory service, air traffic control service (area control service, approach control service or aerodrome control service);

“Air transit route” means a defined route for the air transiting of helicopters;

“Airway” means a control area or portion thereof established in the form of a corridor;

“Altitude” means the vertical distance of a level, a point or an object considered as a point, measured from mean sea level;

“Application” means manipulation and processing of data in support of user requirements (ISO 19104*);

“Apron” means a defined area, on a land aerodrome, intended to accommodate aircraft for purposes of loading or unloading passengers, mail or cargo, fueling, parking or maintenance.

“Area minimum altitude” means the minimum altitude to be used under instrument meteorological conditions, which provides a minimum obstacle clearance within a specified area, normally formed by parallels and meridians;

“Area navigation” means a method of navigation which permits aircraft operation on any desired flight path within the coverage of ground- or space-based navigation aids or within the limits of the capability of self-contained aids, or a combination of these;

“Arrival routes” means routes identified in an instrument approach procedure by which aircraft may proceed from the en-route phase of flight to an initial approach fix;

“air traffic services route” means a specified route designed for channeling the flow of traffic as necessary for the provision of air traffic services;

“air traffic services surveillance system” means a generic term meaning variously, ‘ADS-B’, ‘PSR’, ‘SSR’ or any comparable ground-based system that enables the identification of aircraft;

“Calendar” means discrete temporal reference system that provides the basis for defining temporal position to a resolution of one day (ISO 19108*);

“Change-over point” means the point at which an aircraft navigating on an air traffic services route segment defined by reference to very high frequency omni directional radio ranges is expected to transfer its primary navigational reference from the facility behind the aircraft to the next facility ahead of the aircraft;

“Clearway” means a defined rectangular area on the ground or water under the control of the appropriate authority selected or prepared as a suitable area over which an aeroplane may make a portion of its initial climb to a specified height.

“Contour line” means a line on a map or chart connecting points of equal elevation.

“Culture” means all man-made features constructed on the surface of the Earth, such as cities, railways and canals;

“Cyclic redundancy check” means a mathematical algorithm applied to the digital expression of data that provides a level of assurance against loss or alteration of data;

“Danger area” means an airspace of defined dimensions within which activities dangerous to the flight of aircraft may exist at specified times;

“Data product specification” means detailed description of a data set or data set series together with additional information that will enable it to be created, supplied to and used by another party (ISO 19131*);

“Data quality” means a degree or level of confidence that the data provided meets the requirements of the data user in terms of accuracy, resolution and integrity;

“Data set” means identifiable collection of data (ISO 19101*);

“Data set series” means collection of data sets sharing the same product specification (ISO 19115*);

“Datum” means any quantity or set of quantities that may serve as a reference or basis for the calculation of other quantities (ISO 19104*);

“Digital Elevation Model” means the representation of terrain surface by continuous elevation values at all intersections of a defined grid, referenced to common datum;

“Displaced threshold” means a threshold not located at the extremity of a runway;

“Electronic aeronautical chart display” means an electronic device by which flight crews are enabled to execute, in a convenient and timely manner, route planning, route monitoring and navigation by displaying required information;

“Elevation” means the vertical distance of a point or a level, on or affixed to the surface of the earth, measured from mean sea level;

“Feature” means abstraction of real world phenomena (ISO 19101*);

“Feature attribute” means characteristic of a feature (ISO 19101*);

“Final approach” means that part of an instrument approach procedure which commences at the specified final approach fix or point, or where such a fix or point is not specified—

- (a) at the end of the last procedure turn, base turn or inbound turn of a racetrack procedure, if specified; or
- (b) at the point of interception of the last track specified in the approach procedure; and
- (c) ends at a point in the vicinity of an aerodrome from which:
 - (i) a landing can be made; or
 - (ii) a missed approach procedure is initiated;

“Final approach and take-off area” means a defined area over which the final phase of the approach manoeuvre to hover or landing is completed and from which the take-off manoeuvre is commenced. Where the Final approach and take-off area is to be used by performance Class 1 helicopters, the defined area includes the rejected take-off area available;

“Final approach fix or point” means that fix or point of an instrument approach procedure where the final approach segment commences;

“Final approach segment” means that segment of an instrument approach procedure in which alignment and descent for landing are accomplished;

“Flight information region” means an airspace of defined dimensions within which flight information service and alerting service are provided;

“Flight level” means a surface of constant atmospheric pressure which is related to a specific pressure datum, 1 013.2 hectopascals, and is separated from other such surfaces by specific pressure intervals;

“Geodesic distance” means the shortest distance between any two points on a mathematically defined ellipsoidal surface;

“Geodetic datum” means a minimum set of parameters required to define location and orientation of the local reference system with respect to the global reference system/frame;

“Geoid” means the equipotential surface in the gravity field of the Earth which coincides with the undisturbed mean sea level extended continuously through the continents;

“Geoid undulation” means the distance of the geoid above (positive) or below (negative) the mathematical reference ellipsoid;

“Glide path” means a descent profile determined for vertical guidance during a final approach;

“Gregorian calendar” means calendar in general use; first introduced in 1582 to define a year that more closely approximates the tropical year than the Julian calendar (ISO 19108*);

“Height” means the vertical distance of a level, point or an object considered as a point, measured from a specific datum;

“Helicopter stand” means an aircraft stand which provides for parking a helicopter and where ground taxi operations are completed or where the helicopter touches down and lifts off for air taxi operations;

“Heliport” means an aerodrome or a defined area on a structure intended to be used wholly or in part for the arrival, departure and surface movement of helicopters;

“Holding procedure” means a predetermined manoeuvre which keeps an aircraft within a specified airspace while awaiting further clearance;

“Hot spot” means a location on an aerodrome movement area with a history or potential risk of collision or runway incursion, and where heightened attention by pilots/drivers is necessary;

“Human Factors principles” means principles which apply to aeronautical design, certification, training, operations and maintenance and which seek safe interface between the human and other system components by proper consideration to human performance;

“Hypsometric tints” means a succession of shades or colour gradations used to depict ranges of elevation;

“Initial approach segment” means that segment of an instrument approach procedure between the initial approach fix and the intermediate approach fix or, where applicable, the final approach fix or point;

“Instrument approach procedure” means a series of predetermined manoeuvres by reference to flight instruments with specified protection from obstacles from the initial approach fix, or where applicable, from the beginning of a defined arrival route to a point from which a landing can be completed and thereafter, if a landing is not completed, to a position at which holding or en-route obstacle clearance criteria apply;

“Integrity classification (aeronautical data)” means classification based upon the potential risk resulting from the use of corrupted data. Aeronautical data is classified as—

- (a) routine data: there is a very low probability when using corrupted routine data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe;
- (b) essential data: there is a low probability when using corrupted essential data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe;
- (c) critical data: there is a high probability when using corrupted critical data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe;

“Intermediate approach segment” means that segment of an instrument approach procedure between either the intermediate approach fix and the final approach fix or point, or between the

end of a reversal, racetrack or dead reckoning track procedure and the final approach fix or point, as appropriate;

“Intermediate holding position” means a designated position intended for traffic control at which taxiing aircraft and vehicles shall stop and hold until further cleared to proceed, when so instructed by the aerodrome control tower;

“Isogonal” means a line on a map or chart on which all points have the same magnetic variation for a specified epoch;

“Landing area” means that part of a movement area intended for the landing or take-off of aircraft;

“Landing direction indicator” means a device to indicate visually the direction currently designated for landing and for take-off;

“Level” means a generic term relating to the vertical position of an aircraft in flight and meaning variously, height, altitude or flight level;

“Logon address” means a specified code used for data link logon to an air traffic services unit;

“Magnetic variation” means the angular difference between True North and Magnetic North;

“Manoeuvring area” means that part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, excluding aprons;

“Marking” means a symbol or group of symbols displayed on the surface of the movement area in order to convey aeronautical information.

“Metadata” means data about data (ISO 19115*);

“Minimum en-route altitude” means the altitude for an en-route segment that provides adequate reception of relevant navigation facilities and air traffic services communications, complies with the airspace structure and provides the required obstacle clearance;

“Minimum obstacle clearance altitude” means the minimum altitude for a defined segment of flight that provides the required obstacle clearance;

“Minimum sector altitude” means the lowest altitude which may be used which will provide a minimum clearance of 300 m

(1 000 ft) above all objects located in an area contained within a sector of a circle of 46 km (25 NM) radius centred on significant point, the aerodrome reference point, or the heliport reference point;

“Missed approach point” means that point in an instrument approach procedure at or before which the prescribed missed approach procedure must be initiated in order to ensure that the minimum obstacle clearance is not infringed;

“Missed approach procedure” means the procedure to be followed if the approach cannot be continued;

“Movement area” means that part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, consisting of the manoeuvring area and the apron(s);

“Navigation specification” means a set of aircraft and flight crew requirements needed to support performance-based navigation operations within a defined airspace. There are two kinds of navigation specifications—

- (a) required navigation performance specification. A navigation specification based on area navigation that includes the requirement for performance monitoring and alerting, designated by the prefix RNP, e.g. RNP 4, RNP APCH;
- (b) area navigation specification. A navigation specification based on area navigation that does not include the requirement for performance monitoring and alerting, designated by the prefix RNAV, e.g. RNAV 5, RNAV;

“Obstacle” means all fixed (whether temporary or permanent) and mobile objects, or parts thereof, that—

- (a) are located on an area intended for the surface movement of aircraft; or
- (b) extend above a defined surface intended to protect aircraft in flight; or
- (c) stand outside those defined surfaces and that have been assessed as being a hazard to air navigation;

“Obstacle clearance altitude or obstacle clearance height ” means the lowest altitude or the lowest height above the elevation of the relevant runway threshold or the aerodrome elevation as applicable, used in establishing compliance with appropriate obstacle clearance criteria;

“Obstacle free zone” means the airspace above the inner approach surface, inner transitional surfaces, and balked landing surface and that portion of the strip bounded by these surfaces, which is not penetrated by any fixed obstacle other than a low-mass and frangibly mounted one required for air navigation purposes;

“Orthometric height” means height of a point related to the geoid, generally presented as a mean sea level elevation;

“performance-based navigation” means area navigation based on performance requirements for aircraft operating along an air traffic services route, on an instrument approach procedure or in a designated airspace;

“portrayal” means presentation of information to humans (ISO 19116*);

“position (geographical)” means set of coordinates (latitude and longitude) referenced to the mathematical reference ellipsoid which define the position of a point on the surface of the Earth;*

“precision approach procedure” means an instrument approach procedure utilizing azimuth and glide path information provided by ILS or PAR;

“procedure altitude/height” means specified altitude/height flown operationally at or above the minimum altitude/height and established to accommodate a stabilized descent at a prescribed descent gradient/angle in the intermediate/final approach segment;

“procedure turn” means manoeuvre in which a turn is made away from a designated track followed by a turn in the opposite direction to permit the aircraft to intercept and proceed along the reciprocal of the designated track;

“Prohibited area” means an airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is prohibited;

“relief” means the inequalities in elevation of the surface of the Earth represented on aeronautical charts by contours, hypsometric tints, shading or spot elevations;

“reporting point” means a specified (named) geographical location in relation to which the position of an aircraft can be reported;

“resolution” means a number of units or digits to which a measured or calculated value is expressed and used;

“restricted area” means an airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is restricted in accordance with certain specified conditions;

“reversal procedure” means a procedure designed to enable aircraft to reverse direction during the initial approach segment of an instrument approach procedure. The sequence may include procedure turns or base turns;

“runway” means a defined rectangular area on a land aerodrome prepared for the landing and take-off of aircraft;

“runway-holding position” means a designated position intended to protect a runway, an obstacle limitation surface, or an ILS/MLS critical/sensitive area at which taxiing aircraft and vehicles shall stop and hold, unless otherwise authorized by the aerodrome control tower;

“runway strip” means a defined area including the runway and stopway, if provided, intended:

- (a) to reduce the risk of damage to aircraft running off a runway; and
- (b) to protect aircraft flying over it during take-off or landing operations;

“runway visual range” means the range over which the pilot of an aircraft on the centre line of a runway can see the runway surface markings or the lights delineating the runway or identifying its centre line;

“shoulder” means an area adjacent to the edge of a pavement so prepared as to provide a transition between the pavement and the adjacent surface;

“significant point” means a specified geographical location used in defining an air traffic services route or the flight path of an aircraft and for other navigation and air traffic services purposes;

“stopway” means a defined rectangular area on the ground at the end of take-off run available prepared as a suitable area in which an aircraft can be stopped in the case of an abandoned take-off;

“taxiing” means movement of an aircraft on the surface of an aerodrome under its own power, excluding take-off and landing;

“taxi-route” means a defined path established for the movement of helicopters from one part of a heliport to another. A taxi-route includes a helicopter air or ground taxiway which is centred on the taxi-route;

“taxiway” means a defined path on a land aerodrome established for the taxiing of aircraft and intended to provide a link between one part of the aerodrome and another, including—

- (a) aircraft stand taxiway. A portion of an apron designated as a taxiway and intended to provide access to aircraft stands only;
- (b) apron taxiway. A portion of a taxiway system located on an apron and intended to provide a through taxi route across the apron;
- (c) rapid exit taxiway. A taxiway connected to a runway at an acute angle and designed to allow landing aeroplanes to turn off at higher speeds than are achieved on other exit taxiways thereby minimizing runway occupancy times;

“terminal arrival altitude” means the lowest altitude that will provide a minimum clearance of 300 metres (1 000 feet) above all objects located in an arc of a circle defined by a 46 kilometre (25 nautical miles) radius centred on the Initial Approach Fix, or where there is no Initial Approach Fix on the Intermediate approach Fix, delimited by straight lines joining the extremity of the arc to the Intermediate Approach Fix. The combined Terminal Arrival Altitudes associated with an approach procedure shall account for an area of 360 degrees around the intermediate approach fix;

“terrain” means the surface of the Earth containing naturally occurring features such as mountains, hills, ridges, valleys, bodies of water, permanent ice and snow, and excluding obstacles;

“threshold” means the beginning of that portion of the runway usable for landing;

“touchdown and lift-off area ” means a load bearing area on which a helicopter may touch down or lift off;

“touchdown zone” means the portion of a runway, beyond the threshold, where it is intended landing aeroplanes first contact the runway;

“track” means the projection on the earth’s surface of the path of an aircraft, the direction of which path at any point is usually expressed in degrees from North (true, magnetic or grid);

“transition altitude” means the altitude at or below which the vertical position of an aircraft is controlled by reference to altitudes;

“vectoring” means provision of navigational guidance to aircraft in the form of specific headings, based on the use of an air traffic services surveillance system;

“visual approach procedure” means a series of predetermined manoeuvres by visual reference, from the initial approach fix, or where applicable, from the beginning of a defined arrival route to a point from which a landing can be completed and thereafter, if a landing is not completed, a go-around procedure can be carried out;

“waypoint” means a specified geographical location used to define an area navigation route or the flight path of an aircraft employing area navigation. Waypoints are identified as either–

- (a) fly-by waypoint. A waypoint which requires turn anticipation to allow tangential interception of the next segment of a route or procedure; or
- (b) flyover waypoint. A waypoint at which a turn is initiated in order to join the next segment of a route or procedure.

3. (1) These Regulations shall apply to a person or entity providing an aeronautical cartographic service within designated airspace and at aerodromes for civil aviation purposes in Kenya . Application

(2) No person or entity shall provide an aeronautical cartographic service unless such organization has been certificated to do so by the Authority in accordance with the Civil Aviation (Certifications of Air Navigation Service Providers) Regulations.

(3) A person or entity providing aeronautical cartographic services shall develop and avail charts to the entity coordinating search and rescue activities in the designated airspace as prescribed by the Authority.

4. A certificated cartographic service provider shall ensure Availability.
that—
- (a) on the request of another State provide all information relating to the state of Kenya and the area of jurisdiction for the provision of air traffic services;
 - (b) the availability of charts is as provided in these regulations;
 - (c) for any chart or single sheet of a chart series entirely contained within the territory of the state, either—
 - (i) produce the chart or sheet itself; or
 - (ii) arrange for the production of the chart or sheet by another State or by an agency; or
 - (iii) provide another State prepared to accept an obligation to produce the chart or sheet with the data necessary for its production;
 - (d) for any chart or single sheet of a chart series which includes the territory of a Contracting State, in consultation with that state having jurisdiction over the territory concerned determine the manner in which the chart or sheet will be made available.
 - (e) take all reasonable measures to ensure that the information provided and the aeronautical charts made available are adequate and accurate and that aeronautical charts are maintained up to date by an adequate revision service.

PART II - GENERAL SPECIFICATIONS

5. (1) A certificated aeronautical cartographic service provider shall ensure that each type of chart provides Operational requirements for charts.
information—
- (a) relevant to the function of the chart and the design of the chart observes Human Factors principles to facilitate its optimum use;
 - (b) for the safe and expeditious operation of the aircraft appropriate to the phase of flight as listed below—
 - (i) Phase 1-Taxi from aircraft stand to take off;
 - (ii) Phase 2- Take off and climb to en-route air traffic services route structure;

- (iii) Phase 3-Enroute air traffic services route structure;
 - (iv) Phase 4 -Descent to approach
 - (v) Phase 5 - Approach to land and missed approach
 - (vi) Phase 6 -Landing and taxi to aircraft stand.
- (c) that is accurate, free from distortion and clutter, unambiguous, and readable under all normal operating conditions;
- (d) and that the colours or tints and type size used are such that the chart can be easily read and interpreted by the pilot in varying conditions of natural and artificial light.
- (e) in a form which enables the pilot to acquire information in a reasonable time consistent with workload and operating conditions.
- (f) that permits smooth transition from chart to chart as appropriate to the phase of flight.
- (2) The charts shall be True North orientated.
- (3) The basic sheet size of the charts shall be 210 × 297 mm (8.27 x 11.69 inches) (A4).

6. An aeronautical cartographic service provider shall ensure that the title of a chart or chart series prepared in accordance with these regulations intended to satisfy the function of the chart is that of the relevant part heading except that such title shall not include "ICAO" unless the chart conforms with all requirements specified in part II and any other specified for the particular chart.

Titles

7. An aeronautical cartographic service provider shall ensure that:

Miscellaneous information

- (a) the marginal note layout is as given in first schedule, except as otherwise specified for a particular chart.
- (b) the following information is shown on the face of each chart unless otherwise stated in the specification of the chart concerned:
 - (i) designation or title of the chart series;
 - (ii) name and reference of the sheet;
 - (iii) on each margin an indication of the adjoining sheet where applicable.

(c) a legend to the symbols and abbreviations used is provided on the face or reverse of each chart except that, where it is impracticable for reasons of space, a legend may be published separately; and

(d) the name and adequate address of the producing agency is shown in the margin of the chart except that, where the chart is published as part of an aeronautical document, this information may be placed in the front of that document.

8. An aeronautical cartographic service provider shall ensure that— Symbols.

(a) the symbols used conform to those specified in second schedule of these regulations, except that where it is desired to show on an aeronautical chart special features or items of importance to civil aviation for which no International Civil Aviation Organization symbol is at present provided, any appropriate symbol may be chosen for this purpose, provided that it does not cause confusion with any existing International Civil Aviation Organization chart symbol or impair the legibility of the chart;

(b) the same basic symbol is used on all charts on which it appears, regardless of chart purpose, to represent ground-based navigation aids, intersections and waypoints;

(c) the symbol used for significant points is based on a hierarchy of symbols and selected in the following order:

(i) ground-based navigation aid;

(ii) intersection; and

(iii) waypoint symbol.

(d) a waypoint symbol is used only when a particular significant point does not already exist as either a ground-based navigation aid or intersection; and

(e) the symbols are shown in the manner specified in sub regulation (2), (3) and (4) and in the second schedule - ICAO Chart Symbols, symbol number 121.

9. An aeronautical cartographic service provider shall ensure that the — Units of measurement.

-
- (a) distances are derived as geodesic distances;
- (b) distances are expressed in either kilometres or nautical miles or both, provided the units are clearly differentiated;
- (c) altitudes, elevations and heights are expressed in either metres or feet or both, provided the units are clearly differentiated;
- (d) linear dimensions on aerodromes and short distances are expressed in metres;
- (e) order of resolution of distances, dimensions, elevations and heights are as specified for a particular chart;
- (f) units of measurement used to express distances, altitudes, elevations and heights are conspicuously stated on the face of each chart; and
- (g) conversion scales are provided on each chart on which distances, elevations or altitudes are shown and shall be placed on the face of each chart.
10. An aeronautical cartographic service provider shall ensure that – Scale and projection
- (a) the name and basic parameters and scale of the projection are indicated for charts of large areas; and
- (b) for charts of small areas, a linear scale only is indicated.
11. An aeronautical cartographic service provider shall clearly indicate on the face of each chart the date of validity of aeronautical information. Date of validity of aeronautical information
12. An aeronautical cartographic service provider shall ensure that – Spelling of geographical names
- (a) the symbols of the Roman alphabet are used for all writing;
- (b) the word where a geographical term is abbreviated on any particular chart are spelt out in full; and
- (c) the punctuation marks are not used in abbreviations within the body of a chart.

13. An aeronautical cartographic service provider shall ensure that abbreviations are – Abbreviations.
- (a) used on aeronautical charts whenever they are appropriate; and
 - (b) selected from the Procedures for Air Navigation Services – ICAO document abbreviations and codes number 8400 where applicable.
14. An aeronautical cartographic service provider shall ensure that the - Political boundaries.
- (a) international boundaries are shown, but may be interrupted if data more important to the use of the chart would be obscured; and
 - (b) names identifying the countries are indicated where the territory of more than one State appears on a chart.
15. An aeronautical cartographic service provider shall ensure that the colours used on charts conform to the Colour Guide in third Schedule of these Regulations. Colours.
16. A cartographic service provider shall ensure that- Relief.
- (a) relief, where shown, is portrayed in a manner that will satisfy the chart users' need for–
 - (i) orientation and identification;
 - (ii) safe terrain clearance;
 - (iii) clarity of aeronautical cartographic when shown;
 - (iv) Planning.
 - (b) the tints used where relief is shown by hypsometric tints, are based on those shown in the Hypsometric Tint Guide in fourth Schedule of the Regulation;
 - (c) the spot elevations are shown for selected critical points where spot elevations are used; and
 - (d) the value of spot elevations of doubtful accuracy is followed by the sign.
17. An aeronautical cartographic service provider shall ensure that the reference or other identification are included when prohibited, restricted or danger areas are shown. Prohibited, restricted and danger areas.

18. An aeronautical cartographic service provider shall ensure that the class of airspace, the type, name or call sign, the vertical limits and the radio frequency to be used is indicated when air traffic services airspace is shown on a chart, and the horizontal limits specified in accordance to second schedule of these Regulations.

Air traffic services airspaces.

19. An aeronautical cartographic service provider shall ensure that –

Magnetic variation.

- (a) the True North and magnetic variation are indicated and the order of resolution of magnetic variation is that as specified for a particular chart;
- (b) when magnetic variation is shown on a chart, the values shown are those for the year nearest to the date of publication that is divisible by 5; and
- (c) an interim date and value are quoted in exceptional cases where the current value would be more than one degree different, after applying the calculation for annual change.

20. An aeronautical cartographic service provider shall ensure that –

Aeronautical data.

- (a) all necessary measures are taken to introduce a properly organized quality system containing procedures, processes and resources necessary to implement quality management at each function stage as specified in the Civil Aviation (Aeronautical Information Services) Regulations;
- (b) the execution of such quality management is made demonstrable for each function stage, when required;
- (c) the established procedures exist in order that aeronautical data at any moment is traceable to its origin so to allow any data anomalies or errors, detected during the production and maintenance phases or in the operational use, to be corrected;
- (d) the order of chart resolution of aeronautical data is as specified for a particular chart and as presented in a tabular form in the sixth schedule of these Regulations;
- (e) the integrity of aeronautical data is maintained throughout the data process from survey or origin to the next intended user;

- (f) based on the applicable integrity classification, the validation and verification procedures shall:
 - (i) for routine data: avoid corruption throughout the processing of the data;
 - (ii) for essential data: assure corruption does not occur at any stage of the entire process and include additional processes as needed to address potential risks in the overall system architecture to further assure data integrity at this level; and
 - (iii) critical data: assure corruption does not occur at any stage of the entire process and include additional integrity assurance processes to fully mitigate the effects of faults identified through analysis of the overall system architecture as potential data integrity risks.
- (g) the Aeronautical data quality requirements related to the integrity and data classification is as provided in Tables 1-6 of the sixth schedule of these Regulations; and
- (h) the electronic aeronautical data sets are protected by the inclusion in the data sets of a 32-bit cyclic redundancy check implemented by the application dealing with the data sets and applied to the protection of all integrity levels of data sets as specified in sub-regulation(f) .

21. An aeronautical cartographic service provider shall ensure that the -

Horizontal reference system.

- (a) World Geodetic System — 1984 is used as the horizontal reference system;
- (b) published aeronautical geographical coordinates indicating latitude and longitude are expressed in terms of the World Geodetic System-84 geodetic reference datum;
- (c) geographical coordinates which have been transformed into World Geodetic System -84 coordinates but whose accuracy of original field work does not meet the requirements in the Civil Aviation (Air Traffic Services) Regulations and the Civil Aviation (Aerodrome) Regulations are identified by an asterisk; and

- (d) order of chart resolution of geographical coordinates is as specified for a particular chart series and in accordance with Table 1 of the sixth schedule.

22. An aeronautical cartographic service provider shall ensure that the – Vertical reference system

- (a) mean sea level datum is used as the vertical reference system;
- (b) elevations referenced to mean sea level, for the specific surveyed ground positions, geoid undulation for the surveyed positions are published as specified for a particular chart; and
- (c) order of chart resolution of elevation and geoid undulation is as specified for a particular chart series and in accordance with Table 2 of the sixth schedule in these regulations.

23. An aeronautical cartographic service provider shall ensure that – Temporal reference system

- (a) the Gregorian calendar and Coordinated Universal Time are used as the temporal reference system; and
- (b) when a different temporal reference system is used for charting, this shall be indicated in the Aeronautical Information Publication.

24. An aeronautical cartographic service provider shall publish the following charts, as applicable and in accordance to the requirements as prescribed by the Authority. Charts to be Published

- (a) Aerodrome Obstacle Chart;
- (b) Precision Approach Terrain Chart;
- (c) En-route Chart;
- (d) Area Chart or, alternatively, Standard Departure Chart – Instrument and Standard Arrival Chart – Instrument;
- (e) Instrument Approach Chart;
- (f) Visual Approach Chart;
- (g) Aerodrome/Heliport Chart;
- (h) Aerodrome Ground Movement Chart;
- (i) Aircraft Parking/Docking Chart;

- (j) World Aeronautical Chart or, alternatively, Aeronautical Chart or Aeronautical Navigation Chart;
- (k) Plotting Chart;
- (l) Air Traffic Control Surveillance Minimum Altitude Chart;

25. An aeronautical cartographic service provider shall ensure that an Aeronautical charting automated systems comply with the following requirements:

Use of automation in aeronautical charting.

- (a) provide for continuous and timely updating of the system database and monitoring of the validity and
- (b) quality of the aeronautical information stored;
- (c) integrate data from a wide variety of sources;
- (d) temporally manage information and related products, to make sure that charts are always up to date;
- (e) facilitate inspection of the aeronautical chart content, possibly through the synchronization of the graphical elements with the central database content via specific metadata;
- (f) provide users with definable rules/templates to facilitate the assembling of the final chart product; and
- (g) ensure products and services are equally available to humans and computer systems, through specific digital formats for capturing and processing the information.

PART III - AERODROME OBSTACLE CHART - ICAO TYPE

A

26. An aeronautical cartographic service provider shall ensure that the Aerodrome Obstacle chart as prescribed by the Authority, in combination with the relevant cartographic information published in the Aeronautical Information Publication, provides the data necessary to enable an operator to comply with the operating limitations of the Civil Aviation (Operations of Aircraft) Regulations.

Function.

27. An aeronautical cartographic service provider shall ensure that—

Availability.

- (a) the Aerodrome Obstacle Chart as prescribed by the Authority is made available in the manner specified in

Regulation 4(b) for all aerodromes regularly used by international civil aviation, except for those aerodromes where there are no obstacles in the take-off flight path areas or where the Aerodrome Terrain and Obstacle Chart as prescribed by the Authority is provided in accordance with Part V of these regulations;

- (b) a notification is published in the Aeronautical Information Publication where a chart is not required because no obstacles exist in the take-off flight path area.

28. An aeronautical cartographic service provider shall ensure that the – Units of measurement.

- (a) elevations are shown to the nearest to the nearest foot; and
- (b) linear dimensions are shown to the nearest half-metre.

29. A cartographic service provider shall ensure that the – Coverage and scale.

- (a) extent or coverage of each chart is sufficient to cover all obstacles;
- (b) horizontal scale is within the range of 1:10 000 to 1:15 000;
- (c) vertical scale is ten times the horizontal scale; and
- (d) horizontal and vertical linear scales showing both metres and feet are included in the charts.

30. An aeronautical cartographic service provider shall ensure that the – Format.

- (a) charts depict a plan and profile of each runway, any associated stop way or clearway, the take-off flight path area and obstacles;
- (b) profile for each runway, stop way, clearway and the obstacles in the take-off flight path area are shown above its corresponding plan;
- (c) profile of an alternative take-off flight path area comprises a linear projection of the full take-off flight path and is disposed above its corresponding plan in the manner most suited to the ready interpretation of the information;
- (d) profile grid is ruled over the entire profile area exclusive of the runway;

- (e) zero for vertical coordinates is mean sea level;
- (f) zero for horizontal coordinates is at the end of the runway furthest from the take-off flight path area concerned;
- (g) graduation marks indicating the sub-divisions of intervals is shown along the base of the grid and along the vertical margins;
- (h) chart includes:
 - (i) a box for recording the operational data specified in Regulation 33
 - (ii) a box for recording amendments and dates thereof.

31. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the country in which the aerodrome is located, the name of the city or town or area which the aerodrome serves, the name of the aerodrome and the designator of the runway.

Identification.

32. An aeronautical cartographic service provider shall ensure that the magnetic variation to the nearest degree and date of information is indicated.

Magnetic variation.

Aeronautical Data

33. An aeronautical cartographic service provider shall ensure that –

Obstacles.

- (a) objects in the take-off flight path area which project above a plane surface having a 1.2 per cent slope and having a common origin with the take-off flight path area are regarded as obstacles, except that obstacles lying wholly below the shadow of other obstacles as defined in this regulation need not be shown;
- (b) mobile objects such as boats, trains and trucks, which may project above the 1.2 per cent plane, are considered obstacles but are not considered as being capable of creating a shadow;
- (c) plane surface originating at a horizontal line passing through the top of the obstacle at right angles to the centre line of the take-off flight path area is considered as the shadow of an obstacle; and
- (d) If the obstacle creating a shadow is likely to be removed, objects that would become obstacles by its removal shall be shown.

34. An aeronautical cartographic service provider shall ensure that the - Take-off flight path area.
- (a) take-off flight path area consists of a quadrilateral area on the surface of the earth lying directly below, and symmetrically disposed about the take-off flight path and has the following characteristics—
 - (i) commences at the end of the area declared suitable for take-off ;
 - (ii) the width at the point of origin is 180 m (600 ft) and this width increases at the rate of 0.25D to a maximum of 1 800 m (6 000 ft), where D is the distance from the point of origin;
 - (iii) extends to the point beyond which no obstacles exist or to a distance of 10.0 km (5.4 NM), whichever is the lesser; and
 - (b) For runways serving aircraft having operating limitations which do not preclude the use of a take-off flight path gradient of less than 1.2 per cent, the extent of the take-off flight path area specified in sub regulation 32 (a) (iii) shall be increased to not less than 12.0 km (6.5 NM) and the slope of the plane surface specified in sub regulation 32 (a) (i) and (ii) shall be reduced to 1.0 percent less.
35. An aeronautical cartographic service provider shall ensure that - Declared distances.
- (a) the following information for each direction of each runway is provided—
 - (i) take-off run available;
 - (ii) accelerate-stop distance available;
 - (iii) take-off distance available; and
 - (iv) landing distance available.
 - (b) a runway is identified as “not usable for take-off, landing or both” where a declared distance is not provided because a runway is usable in one direction only.
36. (1) An aeronautical cartographic service provider shall ensure that the plan view shows - Plan and profile views.
- (a) the outline of the runways by a solid line, including the length and width, the magnetic bearing to the nearest degree, and the runway number;

- (b) the outline of the clearways by a broken line, including the length and identification as such;
 - (c) take-off flight path areas by a dashed line and the centre line by a fine line consisting of short and long dashes;
 - (d) alternative take-off flight path areas and where alternative take-off flight path areas not centered on the extension of the runway centre line are shown, notes are provided explaining the significance of such areas;
 - (e) obstacles, including:
 - (i) the exact location of each obstacle together with a symbol indicative of its type;
 - (ii) the elevation and identification of each obstacle;
 - (iii) the limits of penetration of obstacles of large extent in a distinctive manner identified in the legend.
- (2) An aeronautical cartographic service provider shall ensure that –
- (a) the nature of the runway and stop way surfaces are indicated;
 - (b) stop ways are identified as such and are shown by a broken line;
 - (c) the length of each stop way is indicated.
- (3) An aeronautical cartographic service provider shall ensure that the profile view shows –
- (a) the profile of the centre line of the runway by a solid line and the profile of the centre line of any associated stop ways and clearways by a broken line;
 - (b) the elevation of the runway centre line at each end of the runway, at the stop way and at the origin of each take-off;
 - (c) obstacles, including:
 - (i) each obstacle by a solid vertical line extending from a convenient grid line over at least one other grid line to the elevation of the top of the obstacle;
 - (ii) identification of each obstacle;

- (iii) the limits of penetration of obstacles of large extent in a distinctive manner identified in the legend.

37. An aeronautical cartographic service provider shall ensure that the – Accuracy.

- (a) order of accuracy attained is shown on the chart;
- (b) horizontal dimensions and the elevations of the runway, stop way and clearway to be printed on the chart are determined to the nearest 0.5 m (1 ft);
- (c) order of accuracy of the field work and the precision of chart production are such that measurements in the take-off flight path areas can be taken from the chart within the following maximum deviations:
- (i) horizontal distances: 5 m (15 ft) at a point of origin increasing at a rate of 1 per 500;
- (ii) vertical distances: 0.5 m (1.5 ft) in the first 300 m (1 000ft) and increasing at a rate of 1 per 1 000; and
- (d) elevation of the datum used is stated and is identified as assumed where no accurate datum for vertical reference is available.

PART IV - AERODROME OBSTACLE CHART – ICAO TYPE B

38. An aeronautical cartographic service provider shall ensure that the Aerodrome Obstacle Chart – Type B provides information to satisfy the following functions– Function

- (a) the determination of minimum safe altitudes/heights including those for circling procedures;
- (b) the determination of procedures for use in the event of an emergency during take-off or landing;
- (c) the application of obstacle clearing and marking criteria; and
- (d) the provision of source material for aeronautical charts.

39. An aeronautical cartographic service provider shall ensure that the – Availability

- (a) Aerodrome Obstacle Charts as prescribed by the Authority is made available, in the manner prescribed in Regulation 4(b) for all aerodromes regularly used by international civil aviation except for those aerodromes where the Aerodrome Terrain and Obstacle Chart as prescribed by the Authority is provided in accordance with part V

- (b) Aerodrome Obstacle Chart as prescribed by the Authority is called the Aerodrome Obstacle Chart when a chart combining the specifications of part III and Part IV of this Regulation is made available.

40. An aeronautical cartographic service provider shall ensure that the – Units of measurement.

- (a) elevations are shown to the nearest foot; and
(b) linear dimensions are shown to the nearest half-metre.

41. An aeronautical cartographic service provider shall ensure that – Coverage and scale.

- (a) the extent or coverage of each chart is sufficient to cover all obstacles
(b) the horizontal scale is within the range of 1:10 000 to 1:20 000; and
(c) a horizontal linear scale showing both metres and feet is included in the chart and when necessary, a linear scale for kilometres and a linear scale for nautical miles is also shown.

42. An aeronautical cartographic service provider shall ensure that the charts include – Format.

- (a) any necessary explanation of the projection used;
(b) any necessary identification of the grid used;
(c) a notation indicating that obstacles are those which penetrate the surfaces specified in Civil Aviation (Aerodromes) Regulations);
(d) a box for recording amendments and dates thereof; and
(e) outside the neat line, every minute of latitude and longitude marked in degrees and minutes.

43. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the country in which the aerodrome is located, the name of the city or town or area which the aerodrome serves, and the name of the aerodrome. Identification.

44. An aeronautical cartographic service provider shall ensure that the – Culture and topography.

- (a) drainage and hydrographic details are kept to a minimum;
(b) buildings and other salient features associated with the aerodrome are shown and wherever possible, to scale;

- (c) all objects, either cultural or natural, that project above the take-off and approach surfaces specified in regulation 45 or the clearing and marking surfaces specified in Civil Aviation (Aerodrome) Regulations are shown; and
- (d) roads and railroads within the take-off and approach area, and less than 600 m (2 000 ft) from the end of the runway or runway extensions, are shown.

45. An aeronautical cartographic service provider shall ensure that the chart shows a compass rose orientated to the True North, or a North point, showing the magnetic variation to the nearest degree with the date of magnetic cartographic and annual change.

Magnetic variation

46. An aeronautical cartographic service provider shall ensure that the chart shows –

Aeronautical data

- (a) the aerodrome reference point and its geographical coordinates in degrees, minutes and seconds;
- (b) the outline of the runways by a solid line;
- (c) the length and width of the runway;
- (d) the magnetic bearing to the nearest degree of the runway and the runway number;
- (e) the elevation of the runway centre line at each end of the runway, at the stop way, at the origin of each take-off and approach area, and at each significant change of slope of runway and stop way;
- (f) taxiways, aprons and parking areas identified as such, and the outlines by a solid line;
- (g) stop ways identified as such and depicted by a broken line;
- (h) the length of each stop way;
- (i) clearways identified as such and depicted by a broken line;
- (j) the length of each clearway;
- (k) take-off and approach surfaces identified as such and depicted by a broken line;
- (l) take-off and approach areas;

- (m) obstacles at their exact location, including:
 - (i) a symbol indicative of their type;
 - (ii) elevation;
 - (iii) identification;
 - (iv) limits of penetration of large extent in a distinctive manner identified in the legend;
- (n) any additional obstacles, as determined by regulation 31 (a) including the obstacles in the shadow of an obstacle, which would otherwise be exempted.
 - (i) The nature of the runway and stopway surfaces shall be given.
 - (ii) The highest object or obstacle between adjacent approach areas within a radius of 5 000 m (15 000 ft) from the aerodrome reference point shall be indicated in a prominent manner, wherever practicable.
 - (iii) The extent of tree areas and relief features, part of which constitute obstacles, shall be shown.

47. An aeronautical cartographic service provider shall ensure that the – Accuracy.

- (a) order of accuracy attained is shown on the chart;
- (b) horizontal dimensions and the elevations of the movement area, stop ways and clearways to be printed on the chart is determined to the nearest 0.5 m (1 ft);
- (c) order of accuracy of the field work and the precision of chart production is such that the resulting data will be within the maximum deviations indicated herein:
- (d) take-off and approach areas:
 - (i) horizontal distances: 5 m (15 ft) at point of origin increasing at a rate of 1 per 500;
 - (ii) vertical distances: 0.5 m (1.5 ft) in the first 300 m (1 000 ft) and increasing at a rate of 1 per 1 000;
- (e) other areas:
 - (i) horizontal distances: 5 m (15 ft) within 5 000 m (15 000 ft) of the aerodrome reference point and 12 m (40 ft) beyond that area;

(ii) vertical distances: 1 m (3 ft) within 1 500 m (5 000 ft) of the aerodrome reference point increasing at a rate of 1 per 1 000;

(f) elevation of the datum used is stated and identified as assumed, where no accurate datum for vertical reference is available.

PART V - AERODROME TERRAIN AND OBSTACLE CHART – ICAO (ELECTRONIC)

48. An aeronautical cartographic service provider shall ensure that the Aerodrome Terrain and Obstacle Chart electronic portrays the terrain and obstacle data in combination with aeronautical data, as appropriate, necessary to—

- Function.
- (a) enable an operator to comply with the operating limitations of the Civil Aviation (operation of aircraft) Regulations, by developing contingency procedures for use in the event of an emergency during a missed approach or take-off, and by performing aircraft operating limitations analysis; and
 - (b) support the following air navigation applications:
 - (i) instrument procedure design (including circling procedure);
 - (ii) aerodrome obstacle restriction and removal; and
 - (iii) provision of source data for the production of other aeronautical charts.

49. An aeronautical cartographic service provider shall ensure that the—

- Availability.
- (a) aerodrome Terrain and Obstacle Charts as prescribed by the Authority are made available in the manner specified in regulation 4(b) for aerodromes regularly used by international civil aviation;
 - (b) aerodrome Terrain and Obstacle Chart as prescribed by the Authority shall be made available in hard copy format upon request; and
 - (c) ISO 19100 series of standards for geographic cartographic are used as a general data modelling framework.

50. An aeronautical cartographic service provider shall ensure that electronic charts are identified by the name of the country in which the aerodrome is located, the name of the city or town which the aerodrome serves, and the name of the aerodrome.

Identification.

51. An aeronautical cartographic service provider shall ensure that the extent of each chart is sufficient to cover Area 2 as specified in the Civil Aviation (Aeronautical Information Services) Regulations.

Chart Coverage.

52. An aeronautical cartographic service provider shall ensure that the –

General Specifications.

- (a) relationships between features, feature attributes, and the underlying spatial geometry and associated topological relationships are specified by an application schema when developing computer graphic applications that are used to portray features on the chart;
- (b) portrayed information is provided on the basis of portrayal specifications applied according to defined portrayal rules whereby portrayal specifications and portrayal rules are not part of the data set;
- (c) portrayal rules are stored in a portrayal catalogue which making reference to separately stored portrayal specifications; and
- (d) symbols used to portray features are in accordance with regulation 8 and the International Civil Aviation Organization Chart Symbols in second schedule.

53. An aeronautical cartographic service provider shall ensure that –

Terrain feature.

- (a) the terrain feature, and associated attributes, to be portrayed and database-linked to the chart are based on the electronic terrain data sets which satisfy the requirements the Civil Aviation (Aeronautical Information Services) Regulations;
- (b) the terrain feature are portrayed in a manner that provides an effective general impression of a terrain which is too be a representation of terrain surface by continuous elevation values at all intersections of the defined grid, also known as the Digital Elevation Model;
- (c) an ortho-rectified image which matches the features on the digital elevation model with features on the overlying image is to be used to enhance the digital elevation model;
- (d) the portrayed terrain feature is linked to the following associated attributes in the database(s):

- (i) horizontal positions of grid points in geographic coordinates and elevations of the points;
 - (ii) surface type;
 - (iii) contour line values, if provided; and
 - (iv) names of cities, towns and other prominent topographic features.
- (e) other terrain attributes specified in the Civil Aviation (Aeronautical Information Services) Regulations Table A8-3 in the eighth schedule, and provided in the database(s) is linked to the portrayed terrain feature.

54. An aeronautical cartographic service provider shall ensure that the – Obstacle features.

- (a) obstacle features, and associated attributes, portrayed or database -linked to the chart is based on electronic obstacle data sets which satisfy the requirements of the Civil Aviation (Aeronautical Information Services) Regulations;
- (b) each obstacle is portrayed by an appropriate symbol and obstacle identifier;
- (c) the portrayed obstacle feature is linked to the following associated attributes in the database(s):
 - (i) horizontal position in geographic coordinates and associated elevation;
 - (ii) obstacle type; and
 - (iii) obstacle extent, if appropriate;
- (d) other obstacle attributes are as specified in Civil Aviation (Aeronautical Information Services) Regulations table A8-4 in the eighth schedule, and provided in the database linked to the portrayed obstacle feature.

55. An aeronautical cartographic service provider shall ensure that the – Aerodrome features.

- (a) aerodrome features, and associated attributes, portrayed and database -linked to the chart is used on aerodrome data which satisfy the requirements of the Civil Aviation (Aerodrome) Regulations and the Civil Aviation (Aeronautical Information Services) Regulations;

- (b) following aerodrome features are portrayed by an appropriate symbol:
- (i) aerodrome reference point;
 - (ii) runway(s), with designation numbers, and if available, stop way(s) and clearway(s); and
 - (iii) taxiways, aprons, large buildings and other prominent aerodrome features.
- (c) portrayed aerodrome feature is linked to the following associated attributes in the database:-
- (i) geographical coordinates of the aerodrome reference point;
 - (ii) aerodrome magnetic variation, year of cartographic and annual change;
 - (iii) length and width of runway(s), stop way(s) and clearway(s);
 - (iv) type of surface of runway(s) and stop way(s);
 - (v) magnetic bearings of the runway(s) to the nearest degree;
 - (vi) elevations at each end of runway(s), stop way(s) and clearway(s), and at each significant change in slope of runway(s) and stop way(s);
 - (vii) declared distances for each runway direction, or the abbreviation "NU" where a runway direction cannot be used for take-off or landing or both.

56. An aeronautical cartographic service provider shall ensure that the each radio navigation aid feature located within the chart coverage is portrayed by an appropriate symbol.

Radio Navigation and features.

57. An aeronautical cartographic service provider shall ensure that the –

Accuracy and resolution.

- (a) order of accuracy of aeronautical data is as specified in the Civil Aviation (Air Traffic Services), Regulations and the Civil Aviation (Aerodrome) Regulations;
- (b) order of accuracy of terrain and obstacle data is as specified in the Civil Aviation (Aeronautical Information Services) Regulations eighth schedule;
- (c) Aeronautical data resolution is as specified in the Civil Aviation (Aeronautical Information Services) Regulations seventh schedule, and the resolution for

terrain and obstacle data is as specified in Civil Aviation (Aeronautical Information Services) Regulations eighth schedule.

58. An aeronautical cartographic service provider shall ensure that the – Electronic functionality.

- (a) symbols and text size varies with chart scale to enhance readability;
- (b) information on the chart is geo-referenced, and it is possible to determine cursor position to at least the nearest second;
- (c) chart is compatible with widely available desktop computer hardware, software and media;
- (d) chart includes a reader software;
- (e) it is not possible to remove information from the chart without an authorized update;
- (f) selectable information layers are provided to allow for the customized combination of information when due to congestion of information, the details necessary to support the function of the chart cannot be shown with sufficient clarity on a single comprehensive chart view; and
- (g) chart can be printed in hard copy format according to the content specifications and scale determined by the user.

59. An aeronautical cartographic service provider shall ensure that – Chart data product specifications.

- (a) a comprehensive statement of the data sets comprising the chart is provided in the form of data product specifications on which basis air navigation users will be able to evaluate the chart data product and determine whether it fulfils the requirements for its intended use;
- (b) the chart data product specifications includes an overview, a specification scope, a data product identification, data content information, the reference systems used, the data quality requirements, and information on data on data capture, data maintenance, data portrayal, data product delivery, as well as any additional information available, and metadata;
- (c) the overview of the chart data product specifications provides an informal description of the product and

contains the general information about the data product and specification scope of the chart data product specifications contains the spatial extent of the chart coverage;

- (d) the chart data product identification includes the title of the product, a brief narrative summary of the content and purpose, and a description of the geographic area covered by the chart;
- (e) the data content of the chart data product specifications clearly identify the type of coverage and imagery and provide a narrative description of each;
- (f) the chart data product specifications includes information that defines the reference systems used including:-
 - (i) the spatial reference system (horizontal and vertical) and, if appropriate;
 - (ii) temporal reference system.
- (g) the chart data product specifications identifies the data quality requirements including –
 - (i) a statement on acceptable conformance quality levels, and;
 - (ii) corresponding data quality measures.
- (h) statement in paragraph (g) covers all the data quality elements and data quality sub-elements; even if only to state that a specific data quality element or sub-element is not applicable.
- (i) The chart data product specifications includes:
 - (i) a data capture statement which is a general description of the sources and processes applied for the capture of chart data;
 - (ii) The principles and criteria applied in the maintenance of the chart;
 - (iii) the frequency with which the chart product is updated;
 - (iv) the maintenance cartographic of obstacle data sets included on the chart, and;
 - (v) an indication of the principles, methods and criteria applied for obstacle data maintenance.

- (j) chart data product specifications contains:
 - (i) information on how data are portrayed on the chart, as detailed in regulation 50;
 - (ii) the chart data product delivery information which include delivery formats and delivery medium information; and
- (k) core chart metadata elements is included in the chart data product specifications and any additional metadata items required to be supplied is stated in the product specifications together with the format and encoding of the metadata.

PART VI - PRECISION APPROACH TERRAIN CHART
— ICAO

60. An aeronautical cartographic service provider shall ensure that the precision approach terrain chart provides detailed terrain profile information within a defined portion of the final approach so as to enable aircraft operating agencies to assess the effect of the terrain on decision height determination by the use of radio altimeters. Function

61. An aeronautical cartographic service provider shall ensure that the – Availability

- (a) precision approach terrain chart is made available for all precision approach runways Categories II and III at aerodromes used by international civil aviation, except where the requisite information is provided in the Aerodrome Terrain and Obstacle Chart as prescribed by the Authority in accordance with part V of these regulations;
- (b) precision approach terrain chart is revised whenever any significant change occurs.

62. An aeronautical cartographic service provider shall ensure that – Scale.

- (a) the horizontal scale is 1:2500, and the vertical scale 1:500;
- (b) when the chart includes a profile of the terrain to a distance greater than 900 m (3 000 ft) from the runway threshold, the horizontal scale is 1:5000.

63. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the country in which the aerodrome is located, the name of the city or town or area which the aerodrome serves, the name of the aerodrome and the designator of the runway. Identification

64. An aeronautical cartographic service provider shall ensure that the – Plan and profile information.

- (a) chart includes:
- (i) a plan showing contours at 1m (3 ft) intervals in the area 60m (200 ft) on either side of the extended centre line of the runway, to the same distance as the profile, the contours to be related to the runway threshold;
 - (ii) an indication where the terrain or any object thereon, within the plan defined in (i), differs by ± 3 m (10 ft) in height from the centre line profile and is likely to affect a radio altimeter;
 - (iii) a profile of the terrain to a distance of 900 m (3 000 ft) from the threshold along the extended centre line of the runway;
- (b) where the terrain at a distance greater than 900 m (3 000 ft) from the runway threshold is mountainous or otherwise significant to users of the chart, the profile of the terrain is shown to a distance not exceeding 2000m (6500ft) from the runway threshold;
- (c) ILS reference datum height is shown to the nearest foot.

PART VII - ENROUTE CHART — ICAO

65. An aeronautical cartographic service provider shall ensure that the En-route chart provides flight crews with information to facilitate navigation along Air Traffic Service routes in compliance with air traffic services procedures. Function

66. An aeronautical cartographic service provider shall ensure that – Availability

- (a) the enroute chart is made available in the manner prescribed in regulation 4(b) for all areas where flight information regions have been established in (state);
- (b) separate charts are provided where different air traffic services routes, position reporting requirements or lateral limits of flight information regions or control areas exist in different layers of airspace and cannot be shown with sufficient clarity on one chart.

67. An aeronautical cartographic service provider shall ensure that – Coverage and scale.

- (a) the layout of sheet lines is determined by the density and pattern of the air traffic service route structure;

- (b) large variations of scale between adjacent charts showing a continuous route structure are to be avoided; and
- (c) an adequate overlap of charts is provided to ensure continuity of navigation.

68. An aeronautical cartographic service provider shall ensure that the – Projection

- (a) parallels and meridians are shown at suitable intervals; and
- (b) graduation marks are placed at consistent intervals along selected parallels and meridians.

69. An aeronautical cartographic service provider shall ensure that each sheet of the chart is identified by chart series and number. Identification

70. An aeronautical cartographic service provider shall ensure that – Culture and topography

- (a) generalized shore lines of all open water areas, large lakes and rivers are shown except where they conflict with data more applicable to the function of the chart;
- (b) area minimum altitude are shown within each quadrilateral formed by the parallels and meridians;
- (c) selected orientation used is clearly indicated, where charts are not True North orientated.

71. An aeronautical cartographic service provider shall ensure that the isogonals are indicated and the date of the isogonic information given. Magnetic variation

72. An aeronautical cartographic service provider shall ensure that the – Bearng. tracks and radials

- (a) bearings, tracks and radials are:
 - (i) magnetic, except as provided for in sub paragraph (ii);
 - (ii) shown in parentheses to the nearest tenth of a degree where bearings and tracks are additionally provided as true values for area navigation segments;
 - (iii) clearly indicated where bearings, tracks or radials are given with reference to True North or Grid North;
- (b) reference grid meridian is identified when Grid North is used.

Aeronautical data

73. An aeronautical cartographic service provider shall ensure that all aerodromes used by international civil aviation to which an instrument approach can be made are shown.

Aerodromes.

74. An aeronautical cartographic service provider shall ensure that the prohibited, restricted and danger areas relevant to the layer of airspace are depicted with their identification and vertical limits.

Prohibited, restricted and danger areas.

75. An aeronautical cartographic service provider shall ensure that the –

Air traffic services system.

- (a) components of the established air traffic services system are shown where appropriate;
- (b) components include the following:
 - (i) the radio navigation aids associated with the air traffic services system together with their names, identifications, frequencies and geographical coordinates in degrees, minutes and seconds;
 - (ii) in respect of distance measuring equipment, additionally the elevation of the transmitting antenna of the distance measuring equipment to the nearest 30 m (100 ft);
 - (iii) an indication of all designated airspace, including lateral and vertical limits and the appropriate class of airspace;
 - (iv) all air traffic services routes for en-route flight including route designators, the track to the nearest degree in both directions along each segment of the routes and, where established, the designation of the navigation specification(s) including any limitations and the direction of traffic flow;
 - (v) all significant points which define the air traffic services routes and are not marked by the position of a radio navigation aid, together with their name-codes and geographical coordinates in degrees, minutes and seconds;
 - (vi) in respect of waypoints defining VOR/distance measuring equipment area navigation routes, additionally,
 - (vii) the station identification and radio frequency of the reference VOR/distance measuring

equipment;

- (viii) the bearing to the nearest tenth of a degree and the distance to the nearest two-tenths of a kilometre (tenth of a nautical mile) from the reference VOR/ distance measuring equipment, if the waypoint is not collocated with it;
- (ix) an indication of all compulsory and "on-request" reporting points and air transport services/MET reporting points;
- (x) the distances to the nearest kilometre or nautical mile between significant points constituting turning points or reporting points;
- (xi) change-over points on route segments defined by reference to very high frequency omnidirectional radio ranges, indicating the distances to the nearest kilometre or nautical mile to the navigation aids;
- (xii) minimum en-route altitudes and minimum obstacle clearance altitudes, on air transport services routes to the nearest higher 50 metres or 100 feet (the Civil Aviation (Air Traffic Service Regulations));
- (xiii) communication facilities listed with their channels and, if applicable, logon address and satellite voice communications number; and
- (xiv) air defense identification zone properly identified.

76. An aeronautical cartographic service provider shall ensure that the – Supplementary information

- (a) details of departure and arrival routes and associated holding patterns in terminal areas are shown unless they are shown on an Area Chart, a Standard Departure Chart — Instrument or a Standard Arrival Chart — Instrument; and
- (b) altimeter setting regions are shown and identified where established.

PART VIII—AREA CHART

77. An aeronautical cartographic service provider shall ensure that the area chart provides the flight crew with information to facilitate the following phases of instrument Function

flight—

- (a) the transition between the en-route phase and approach to an aerodrome;
- (b) the transition between take-off/missed approach and en-route phase of flight; and
- (c) flights through areas of complex air traffic services routes or airspace structure.

78. An aeronautical cartographic service provider shall ensure that — Availability.

- (a) the area chart is made available in the manner specified in regulation 4(b) where the air traffic services routes or position reporting requirements are complex and cannot be adequately shown on an Enroute Chart;
- (b) separate charts are provided where air traffic services routes or position reporting requirements are different for arrivals and for departures, and cannot be shown with sufficient clarity on one chart.

79. An aeronautical cartographic service provider shall ensure that the: Coverage and scale.

- (a) coverage of each chart extends to points that effectively show departure and arrival routes;
- (b) chart is drawn to scale and a scale-bar shown.

80. An aeronautical cartographic service provider shall ensure that — Projection.

- (a) a conformal projection on which a straight line approximates a great circle is used;
- (b) the parallels and meridians are shown at suitable intervals; and
- (c) graduation marks are placed at consistent intervals along the neat lines, as appropriate.

81. A chart shall be identified by a name associated with the airspace portrayed. Identification.

82. An aeronautical cartographic service provider shall ensure that — Culture and topography.

- (a) generalized shorelines of all open water areas, large lakes and rivers are shown except where they conflict with data more applicable to the function of the charts;

- (b) all relief exceeding 300 m (1 000 ft) above the elevation of the primary aerodrome is shown by smoothed contour lines, contour values and layer tints printed in brown, in areas where significant relief exists;
- (c) appropriate spot elevations, including the highest elevation within each top contour line, are shown printed in black and obstacles shown.
83. An aeronautical cartographic service provider shall ensure that the average magnetic variation of the area covered by the chart is shown to the nearest degree. Magnetic variation.
84. An aeronautical cartographic service provider shall ensure that— Bearings, tracks and radials.
- (a) bearings, tracks and radials are:
- (i) magnetic;
- (ii) shown in parentheses to the nearest tenth of a degree where bearings and tracks are additionally provided as true values for area navigation segments;
- (b) where bearings, tracks or radials are given with reference to True North or Grid North, this shall be clearly indicated;
- (c) when Grid North is used, its reference grid meridian shall be identified.
85. An aeronautical cartographic service provider shall ensure that the all aerodromes which affect the terminal routings are shown and where appropriate, a runway pattern symbol is used. Aerodromes.
86. An aeronautical cartographic service provider shall ensure that prohibited, restricted and danger areas are depicted with their identification and vertical limits. Prohibited, restricted and danger areas.
87. An aeronautical cartographic service provider shall ensure that the area minimum altitudes are shown within quadrilaterals formed by the parallels and meridians. Area minimum altitudes.
88. An aeronautical cartographic service provider shall ensure that the — Air traffic services system.
- (a) components of the established relevant air traffic services system are shown;
- (b) components referred to in sub regulation (a) include the following—

- (i) the radio navigation aids associated with the air traffic services system, together with their names, identifications, frequencies and geographical coordinates in degrees, minutes and seconds;
- (ii) the elevation of the transmitting antenna of the distance measuring equipment to the nearest 30 m (100 ft);
- (iii) terminal radio aids which are required for outbound and inbound traffic and for holding patterns;
- (iv) the lateral and vertical limits of all designated airspace and the appropriate class of airspace;
- (v) the designation of the navigation specification(s) including any limitations, where established;
- (vi) holding patterns and terminal routings, together with the route designators, and the track to the nearest degree along each segment of the prescribed airways and terminal routings;
- (vii) all significant points which define the terminal routings and are not marked by the position of a radio navigation aid, together with their name-codes and geographical coordinates in degrees, minutes and seconds;
- (viii) in respect of waypoints defining VOR/distance measuring equipment area navigation routes, additionally,
- (ix) the station identification and radio frequency of the reference VOR/distance measuring equipment;
- (x) the bearing to the nearest tenth of a degree and the distance to the nearest two-tenths of a kilometre (tenth of a nautical mile) from the reference VOR/distance measuring equipment, if the waypoint is not collocated with it;
- (xi) an indication of all compulsory and "on-request" reporting points;

- (xii) the distances to the nearest kilometre or nautical mile between significant points constituting turning points or reporting points;
- (xiii) change-over points on route segments defined by reference to very high frequency omnidirectional radio ranges, indicating the distances to the nearest kilometre or nautical mile to the radio navigation aids;
- (xiv) minimum en-route altitudes and minimum obstacle clearance altitudes, on air traffic services routes to the nearest higher 50 metres or 100 feet ;
- (xv) established minimum vectoring altitudes to the nearest higher 50 m or 100 ft, clearly identified;
- (xvi) area speed and level/altitude restrictions where established;
- (xvii) communication facilities listed with their channels and, if applicable, logon address and satellite voice communications number; and
- (xviii) an indication of “flyover” significant points.

PART IX—STANDARD DEPARTURE CHART—
INSTRUMENT (SID)

89. An aeronautical cartographic service provider shall ensure that the standard departure chart - instrument provides the flight crew with information to enable it to comply with the designated standard departure route instrument from take-off phase to the en-route phase.

Function.

90. An aeronautical cartographic service provider shall ensure that the standard departure Chart — instrument is made available wherever standard departure route — instrument has been established and cannot be shown with sufficient clarity on the Area Chart.

Availability.

91. An aeronautical cartographic service provider shall ensure that –

Coverage and scale.

- (a) the coverage of the chart is sufficient to indicate the point where the departure route begins and the specified significant point at which the en-route phase of flight along a designated air traffic services route can be commenced;
- (b) if the chart is drawn to scale a scale-bar is shown; and

- (c) when the chart is not to scale, the annotation "NOT TO SCALE" is shown and the symbol for scale break is used on tracks and other aspects of the chart which are too large to be drawn to scale.

92. An aeronautical cartographic service provider shall ensure that graduation marks are placed at consistent intervals along the neat lines. Projection.

93. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the city or town or area which the aerodrome serves, the name of the aerodrome and the identification of the standard departure route(s) — instrument as established in accordance with the Procedures for Air Navigation Services — Aircraft Operations Volume II, Part I, Section 3, Chapter 5. Identification.

94. An aeronautical cartographic service provider shall ensure that the generalized shore lines of all open water areas, large lakes and rivers are shown where the chart is drawn to scale except where they conflict with data more applicable to the function of the chart; Culture and topography.

95. An aeronautical cartographic service provider shall ensure that the magnetic variation used in determining the magnetic bearings, tracks and radials is shown to the nearest degree. Magnetic variation.

96. An aeronautical cartographic service provider shall ensure that — Bearings, tracks and radials.

(a) bearings, tracks and radials are:

(i) magnetic and the bearings and tracks are shown in parentheses to the nearest tenth of a degree where bearings and tracks are additionally provided as true values for area navigation segments;

(ii) clearly indicated where bearings, tracks or radials are given with reference to True North or Grid North; and

(b) the reference grid meridian is identified when Grid North is used.

97. An aeronautical cartographic service provider shall ensure that — Aerodromes.

(a) the aerodrome of departure is shown by the runway pattern; and

(b) all aerodromes which affect the designated standard departure route — instrument are shown and identified

and where appropriate, the aerodrome runway patterns are shown.

98. An aeronautical cartographic service provider shall ensure that the prohibited, restricted and danger areas which may affect the execution of the procedures are shown with their identification and vertical limits.

Prohibited, restricted and danger areas.

99. An aeronautical cartographic service provider shall ensure that the –

Minimum sector altitude.

- (a) established minimum sector altitude is shown with a clear indication of the sector to which minimum sector altitude applies;
- (b) chart is drawn to scale and area minimum altitudes are shown within quadrilaterals formed by the parallels and meridians; and
- (c) area minimum altitudes are shown in those parts of the chart not covered by the minimum sector altitude where the minimum sector altitude has not been established.

100. An aeronautical cartographic service provider shall ensure that the –

Air traffic services systems.

- (a) components of the established relevant air traffic services system are shown; and
- (b) components shall comprise of a graphic portrayal of each standard departure route — instrument, including:
 - (i) for departure procedures designed specifically for helicopters the term “CAT H” shall be depicted in the departure chart plan view;
 - (ii) route designator;
 - (iii) significant points defining the route;
 - (iv) track or radial to the nearest degree along each segment of the route;
 - (v) distances to the nearest kilometre or nautical mile between significant points;
 - (vi) minimum obstacle clearance altitudes, along the route or route segments and altitudes required by the procedure to the nearest higher 50 m or 100 feet and flight level restrictions where established;
 - (vii) where the chart is drawn to scale and vectoring on departure is provided, established minimum

- vectored altitudes to the nearest higher 50 m or 100 ft, clearly identified;
- (c) components shall comprise of a the radio navigation aid(s) associated with the route(s) including—
 - (i) plain language name;
 - (ii) identification;
 - (iii) frequency;
 - (iv) geographical coordinates in degrees, minutes and seconds;
 - (v) for distance measuring equipment, the channel and the elevation of the transmitting antenna of the distance measuring equipment to the nearest 30 m (100 ft);
 - (d) the name-codes of the significant points not marked by the position of a radio navigation aid, their geographical coordinates in degrees, minutes and seconds and the bearing to the nearest tenth of a degree and distance to the nearest two-tenths of a kilometre (tenth of a nautical mile) from the reference radio navigation aid;
 - (e) applicable holding patterns;
 - (f) transition altitude/height to the nearest higher 300 m or 1 000 ft;
 - (g) the position and height of close-in obstacles which penetrate the obstacle identification surface . A note shall be included whenever close-in obstacles penetrating the obstacle identification surface exist but which were not considered for the published procedure design gradient;
 - (h) area speed restrictions, where established;
 - (i) the designation of the navigation specification(s) including any limitations, where established;
 - (j) all compulsory and “on-request” reporting points;
 - (k) radio communication procedures, including:
 - (i) call sign(s) of air traffic services unit(s);

- (ii) frequency and if applicable, satellite voice communications number;
- (iii) transponder setting, where appropriate;
- (l) an indication of “flyover” significant points.

101. An aeronautical cartographic service provider shall ensure that the Appropriate data to support navigation database coding is published in accordance with the procedures for Air Navigation Services — Aircraft Operations Document 8168, Volume II, Part III, Section 5, Chapter 2, 2.1, on the reverse of the chart or as a separate, properly referenced sheet.

Aeronautical database requirements

PART X - STANDARD ARRIVAL CHART —
INSTRUMENT (STAR) — ICAO

102. An aeronautical cartographic service provider shall ensure that the chart provides the flight crew with information to enable the flight crew to comply with the designated standard arrival route instrument from the en-route phase to the approach phase.

Function

103. An aeronautical cartographic service provider shall ensure that the Standard Arrival Chart — Instrument is made available wherever a standard arrival route — instrument has been established and cannot be shown with sufficient clarity on the Area Chart.

Availability

104. An aeronautical cartographic service provider shall ensure that —

Coverage and scale

- (a) the coverage of the chart is sufficient to indicate the points where the en-route phase ends and the approach phase begins;
- (b) if the chart is drawn to scale a scale-bar is shown; and
- (c) when the chart is not to scale, the annotation “NOT TO SCALE” is shown and the symbol for scale break is used on tracks and other aspects of the chart which are too large to be drawn to scale.

105. An aeronautical cartographic service provider shall ensure that the graduation marks are placed at consistent intervals along the neat lines.

Projection

106. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the city or town or area which the aerodrome serves, the name of the aerodrome, and the identification of the standard arrival route(s) —

Identification

instrument as established in accordance with the Procedures for Air Navigation Services — Aircraft Operations Document 8168, Volume II, Part I, Section 4, Chapter 2.

107. An aeronautical cartographic service provider shall ensure that the generalized shore lines of all open water areas, large lakes and rivers are shown where the chart is drawn to scale, except where they conflict with data more applicable to the function of the chart.

Culture and topography.

108. The Magnetic variation used in determining the magnetic bearings, tracks and radials shall be shown to the nearest degree.

Magnetic variation.

109. An aeronautical cartographic service provider shall ensure that the —

Bearing, tracks and radials.

- (a) bearings, tracks and radials are magnetic;
- (b) bearings and tracks are shown in parentheses to the nearest tenth of a degree where bearings and tracks are additionally provided as true values for area navigation segments;
- (c) bearings, tracks or radials are clearly indicated where bearings, tracks or radials are given with reference to True North or Grid North; and
- (d) reference grid meridian is identified when Grid North is used.

Aeronautical data

110. An aeronautical cartographic service provider shall ensure that —

Aerodromes.

- (a) the aerodrome of landing is shown by the runway pattern;
- (b) all aerodromes which affect the designated standard arrival route — instrument are shown and identified and where appropriate, the aerodrome runway patterns are shown.

111. An aeronautical cartographic service provider shall ensure that the prohibited, restricted and danger areas which may affect the execution of the procedures are shown with their identification and vertical limits.

Prohibited, restricted and danger areas.

112. An aeronautical cartographic service provider shall ensure that the —

Minimum sector altitude.

- (a) established minimum sector altitude is shown with a clear indication of the sector to which the minimum sector altitude applies;

- (b) chart is drawn to scale and area minimum altitudes are shown within quadrilaterals formed by the parallels and meridians where the minimum sector altitude has not been established; and
- (c) area minimum altitudes are shown in those parts of the chart not covered by the minimum sector altitude.

113. An aeronautical cartographic service provider shall ensure that the –

Air traffic services system.

- (a) components of the established relevant air traffic services system shall be shown.
- (b) components shall comprise of graphic portrayal of each standard arrival route — instrument, including—
 - (i) route designator;
 - (ii) significant points defining the route;
 - (iii) track or radial to the nearest degree along each segment of the route;
 - (iv) distances to the nearest kilometre or nautical mile between significant points;
 - (v) minimum obstacle clearance altitudes, along the route or route segments and altitudes required by the procedure to the nearest higher 50 m or 100 feet and flight level restrictions where established;
 - (vi) where the chart is drawn to scale and vectoring on arrival is provided, established minimum vectoring altitudes to the nearest higher 50 m or 100 ft, clearly identified;
- (c) the components shall comprise of the radio navigation aid(s) associated with the route(s) including—
 - (i) plain language name;
 - (ii) identification;
 - (iii) frequency;
 - (iv) geographical coordinates in degrees, minutes and seconds;
 - (v) for distance measuring equipment, the channel and the elevation of the transmitting antenna of the distance measuring equipment to the nearest 30 m (100 ft);

- (d) the name-codes of the significant points not marked by the position of a radio navigation aid, their geographical coordinates in degrees, minutes and seconds and the bearing to the nearest tenth of a degree and distance to the nearest two-tenths of a kilometre (tenth of a nautical mile) from the reference radio navigation aid;
- (e) applicable holding patterns;
- (f) transition altitude/height to the nearest higher 300 m or 1 000 ft;
- (g) area speed restrictions, where established;
- (h) the designation of the navigation specification(s) including any limitations, where established;
- (i) all compulsory and “on-request” reporting points;
- (j) radio communication procedures, including—
 - (i) call sign(s) of air traffic services unit(s);
 - (ii) frequency and if applicable, satellite voice communications number;
 - (iii) transponder setting, where appropriate;
- (k) an indication of “flyover” significant waypoints; and
- (l) for arrival procedures to an instrument approach designed specifically for helicopters the term “CAT H” shall be depicted in the arrival chart plan view.

114. An aeronautical cartographic service provider shall ensure that appropriate data to support navigation database coding is published in accordance with the Procedures for Air Navigation Services — Aircraft Operations Document 8168, Volume II, Part III, on the reverse of the chart or as a separate, properly referenced sheet.

Aeronautical database requirements.

PART XI—INSTRUMENT APPROACH CHART—ICAO

115. An aeronautical cartographic service provider shall ensure that the Instrument Approach chart provides flight crews with information which will enable the flight crew to perform an approved instrument approach procedure to the runway of intended landing including the missed approach procedure and, where applicable, associated holding patterns.

Function

116. An aeronautical cartographic service provider shall ensure that – Availability.

- (a) the instrument Approach Charts are made available for all aerodromes used by international civil aviation where instrument approach procedures have been established by the Authority;
- (b) a separate Instrument Approach Chart is provided for each precision approach procedure established by the Authority;
- (c) a separate Instrument Approach Chart is provided for each non-precision approach procedure established by the Authority;
- (d) more than one chart is provided when the values for track, time or altitude differ between categories of aircraft on other than the final approach segment of the instrument approach procedures and the listing of these differences on a single chart could cause clutter or confusion; and
- (e) the instrument Approach Charts are revised whenever information essential to safe operation becomes out of date.

117. An aeronautical cartographic service provider shall ensure that – Coverage and scale.

- (a) the coverage of the chart is sufficient to include all segments of the instrument approach procedure and such additional areas as may be necessary for the type of approach intended;
- (b) the scale selected ensures optimum legibility consistent with-
 - (i) the procedure shown on the chart;
 - (ii) Sheet size.
- (c) a scale indication is given;
- (d) a distance circle with a radius of 20 kilometres (10 nautical miles) centered on a distance measuring equipment located on or close to the aerodrome, or on the aerodrome reference point where no suitable distance measuring equipment is available, is shown and the radius of the distance measuring equipment indicated on the circumference, except where this is not practicable; and

(e) a distance scale is shown directly below the profile.

118. An aeronautical cartographic service provider shall ensure that the sheet size is 210 × 297 mm (8.27 x 11.69 inches) (A4). Format.

119. An aeronautical cartographic service provider shall ensure that a conformal projection on which a straight line approximates a great circle is used. Projection.

120. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the city or town or area which the aerodrome serves, the name of the aerodrome and the identification of the instrument approach procedure as established in accordance with the Procedures for Air Navigation Services — Aircraft Operations Document 8168, Volume II, Part I, Section 4, Chapter 9. Identification.

121. An aeronautical cartographic service provider shall ensure that— Culture and topography.

(a) culture and topographic information pertinent to the safe execution of the instrument approach procedure, including the missed approach procedure, associated holding procedures and visual maneuvering procedure when established, is shown;

(b) topographic information is named, only when necessary, to facilitate the understanding of such information, and the minimum is delineation of land masses and significant lakes and rivers;

(c) relief is shown in a manner best suited to the particular elevation characteristics of the area;

(d) In areas where relief exceeds 1 200 m (4 000 ft) above the aerodrome elevation within the coverage of the chart or 600 m (2 000 ft) within 11 km (6 NM) of the aerodrome reference point or when final approach or missed approach procedure gradient is steeper than optimal due to terrain, all relief exceeding 150 m (500 ft) above the aerodrome elevation shall be shown by smoothed contour lines, contour values and layer tints printed in brown.

(e) appropriate spot elevations, including the highest elevation within each top contour line, is shown printed in black.

122. An aeronautical cartographic service provider shall ensure that the — Magnetic variation.

- (a) magnetic variation is shown; and
- (b) value of the variation, indicated to the nearest degree, agrees with that used in determining magnetic bearings, tracks and radials, when shown.

123. An aeronautical cartographic service provider shall ensure that the – Bearings, tracks and radials.

- (a) bearings, tracks and radials are magnetic;
- (b) bearings and tracks are shown in parentheses to the nearest tenth of a degree where bearings and tracks are additionally provided as true values for area navigation segments;
- (c) bearings, tracks or radials are clearly indicated where bearings, tracks or radials are given with reference to True North or Grid North; and
- (d) reference grid meridian is identified when Grid North is used.

Aeronautical data

124. An aeronautical cartographic service provider shall ensure that – Aerodromes.

- (a) all aerodromes which show a distinctive pattern from the air are shown by the appropriate symbol and abandoned aerodromes are identified as abandoned;
- (b) the runway pattern, at a scale sufficiently large to show it clearly is shown for-
 - (i) the aerodrome on which the procedure is based;
 - (ii) aerodromes affecting the traffic pattern or so situated as to be likely, under adverse weather conditions, to be mistaken for the aerodrome of intended landing;
- (c) the aerodrome elevation is shown to the nearest foot in a prominent position on the chart; and
- (d) the threshold elevation or, where applicable, the highest elevation of the touchdown zone is shown to the nearest meter or foot.

125. An aeronautical cartographic service provider shall ensure that the – Obstacles.

- (a) obstacles are shown on the plan view of the chart;
- (b) obstacles are identified if one or more obstacles are the determining factor of an obstacle clearance altitude or height;

- (c) the elevation of the top of obstacles are shown to the nearest metre or foot;
- (d) the heights of obstacles above a datum other than mean sea level are shown and, are given in parentheses on the chart when shown;
- (e) the datum is the aerodrome elevation when the heights of obstacles above a datum other than mean sea level are shown, except that, at aerodromes having an instrument runway with a threshold elevation more than 2 m (7 ft) below the aerodrome elevation, the chart datum is the threshold elevation of the runway to which the instrument approach is related;
- (f) the datum is stated in a prominent position on the chart, where a datum other than mean sea level is used;
- (g) the obstacle free zone is indicated, where an obstacle free zone has not been established for a precision approach runway Category I; and
- (h) Obstacles that penetrate the visual segment surface shall be identified on the chart.

126. An aeronautical cartographic service provider shall ensure that prohibited areas, restricted areas, and danger areas which may affect the execution of the procedures are shown with their identification and vertical limits.

Prohibited, restricted and danger areas.

127. An aeronautical cartographic service provider shall ensure that the –

Radio communication facilities and navigation aids.

- (a) radio navigation aids required for the procedures together with their frequencies, identifications and track-defining characteristics, if any, are shown;
- (b) the facility to be used for track guidance for final approach is clearly identified in the case of a procedure in which more than one station is located on the final approach track;
- (c) consideration is given to the elimination from the approach chart of those facilities that are not used by the procedure;
- (d) the initial approach fix, the intermediate approach fix, the final approach fix or final approach point for an ILS approach procedure, the missed approach point, where established, and other essential fixes or points comprising the procedure are shown and identified;

- (e) the final approach fix or final approach point for an ILS approach procedure are identified with its geographical coordinates in degrees, minutes and seconds;
- (f) radio navigation aids that might be used in diversionary procedures together with their track-defining characteristics, if any, are shown or indicated on the chart;
- (g) radio communication frequencies, including call signs that are required for the execution of the procedures are shown;
- (h) the distance to the aerodrome from each radio navigation aid concerned with the final approach is shown to the nearest kilometre or nautical mile when required by the procedures; and
- (i) the bearing is also be shown to the nearest degree when no track-defining aid indicates the bearing of the aerodrome.

128. An aeronautical cartographic service provider shall ensure that the minimum sector altitude or terminal arrival altitude established is shown, with a clear indication of the sector to which the minimum sector altitude or terminal arrival altitude applies.

Minimum sector altitude or terminal arrival altitude.

129. An aeronautical cartographic service provider shall ensure that the –

Portrayal of procedure tracks.

- (a) plan view shows the following information in the manner indicated –
 - (i) the approach procedure track by an arrowed continuous line indicating the direction of flight;
 - (ii) the missed approach procedure track by an arrowed broken line;
 - (iii) any additional procedure track, other than those specified in i) and ii), by an arrowed dotted line;
 - (iv) bearings, tracks, radials to the nearest degree and distances to the nearest two-tenths of a kilometre or tenth of a nautical mile or times required for the procedure;
 - (v) where no track-defining aid is available, the magnetic bearing to the nearest degree to the

- aerodrome from the radio navigation aids concerned with the final approach;
- (vi) the boundaries of any sector in which visual maneuvering is prohibited;
 - (vii) where specified, the holding pattern and minimum holding altitude/height associated with the approach and missed approach;
 - (viii) caution notes where required, prominently displayed on the face of the chart; and
 - (ix) an indication of "flyover" significant points;
- (b) plan view shows the distance to the aerodrome from each radio navigation aid concerned with the final approach;
- (c) a profile is provided normally below the plan view showing the following data:
- (i) the aerodrome by a solid block at aerodrome elevation;
 - (ii) the profile of the approach procedure segments by an arrowed continuous line indicating the direction of flight;
 - (iii) the profile of the missed approach procedure segment by an arrowed broken line and a description of the procedure;
 - (iv) the profile of any additional procedure segment, other than those specified in ii) and iii), by an arrowed dotted line;
 - (v) bearings, tracks, radials to the nearest degree and distances to the nearest two-tenths of a kilometre or tenth of a nautical mile or times required for the procedure;
 - (vi) altitudes/heights required by the procedures, including transition altitude and procedure altitudes/heights,- and heliport crossing height where established;
 - (vii) limiting distance to the nearest kilometre or nautical mile on procedure turn, when specified;

- (viii) the intermediate approach fix or point, on procedures where no course reversal is authorized;
 - (ix) a line representing the aerodrome elevation or threshold elevation, as appropriate, extended across the width of the chart including a distance scale with its origin at the runway threshold.
- (d) heights required by procedures are shown in parentheses, using the height datum selected in accordance with regulation 123;
- (e) profile view includes a ground profile or a minimum altitude or height portrayal as follows—
- (i) a ground profile shown by a solid line depicting the highest elevations of the relief occurring within the primary area of the final approach segment. The highest elevations of the relief occurring in the secondary areas of the final approach segment shown by a dashed line; or
 - (ii) minimum altitudes or heights in the intermediate and final approach segments indicated within bounded shaded blocks.
130. An aeronautical cartographic service provider shall ensure that the –
- (a) aerodrome operating minima when established by the Authority is shown.
 - (b) obstacle clearance altitudes or heights for the aircraft categories for which the procedure is designed are shown;
 - (c) for precision approach procedures, the obstacle clearance altitudes or heights for Cat DL aircraft of wing span between 65 m and 80 m and vertical distance between the flight path of the wheels and the glide path antenna between 7 m and 8 m is published, when necessary.
131. An aeronautical cartographic service provider shall ensure that –
- (a) where the missed approach point is defined by:
 - (i) a distance from the final approach fix is shown or
 - (ii) a facility or a fix and the corresponding distance from the final approach fix;

Aerodrome operating minima

Supplementary cartographic

- (b) the distance to the nearest two-tenths of a kilometre or tenth of a nautical mile and a table showing ground speeds and times from the final approach fix to the missed approach point is shown.
- (c) a table showing altitudes or heights for each 2 km or 1 NM is shown as appropriate when distance measuring equipment is required for use in the final approach segment;
- (d) the table is not include distances which would correspond to altitudes/heights below the obstacle clearance altitudes or heights;
- (e) a table showing the altitudes or heights is included for procedures in which distance measuring equipment is not required for use in the final approach segment but where a suitably located distance measuring equipment is available to provide advisory descent profile cartographic;
- (f) a rate of descent table is shown;
- (g) the final approach descent gradient to the nearest one-tenth of a per cent and, in parentheses, descent angle to the nearest one-tenth of a degree is shown for non-precision approach procedures with a final approach fix;
- (h) the reference datum height to the nearest half metre or foot and the glide path or elevation or vertical path angle to the nearest one-tenth of a degree is shown for precision approach procedures and approach procedures with vertical guidance;
- (i) a clear indication is given whether it applies to the ILS, the associated ILS localizer only procedure, or both when a final approach fix is specified at the final approach point for ILS;
- (j) in the case of MLS, a clear indication is given when an FAF has been specified at the final approach point; and
- (k) a cautionary note is included, if the final approach descent gradient or angle for any type of instrument approach procedure exceeds the maximum value specified in the Procedures for Air Navigation Services — Aircraft Document 8168 Volume II, Part I, Section 4, Chapter 5.

132. An aeronautical cartographic service provider shall ensure that appropriate data to support navigation database coding is published in accordance with the Procedures for Air Navigation Services — Aircraft Operations Document 8168 Volume II, Part I, Section 4, Chapter 9, for non-RNAV procedures, on the reverse of the chart or as a separate, properly referenced sheet. Aeronautical database requirements
- PART XII - VISUAL APPROACH CHART – ICAO
133. An aeronautical cartographic service provider shall ensure that the Visual Approach chart provides flight crews with information which will enable the flight crew to transit from the en-route or descent to approach phases of flight to the runway of intended landing by means of visual reference. Function
134. An aeronautical cartographic service provider shall ensure that the Visual Approach Chart — is made available in the manner specified in regulation 4(b) for all aerodromes used by international civil aviation where-
- (a) only limited navigation facilities are available; or
 - (b) radio communication facilities are not available; or
 - (c) no adequate aeronautical charts of the aerodrome and its surroundings at 1:500,000 or greater scale are available; or
 - (d) visual approach procedures have been established. Availability
135. An aeronautical cartographic service provider shall ensure that the scale is sufficiently large to permit depiction of significant features and indication of the aerodrome layout. Scale
136. An aeronautical cartographic service provider shall ensure that the basic sheet size is 210 × 297 mm (8.27 x 11.69 inches) (A4). Format
137. An aeronautical cartographic service provider shall ensure that a conformal projection on which a straight line approximates a great circle is used. Projection
138. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the city or town which the aerodrome serves and the name of the aerodrome. Identification.
139. An aeronautical cartographic service provider shall ensure that the – Culture and topography
- (a) natural and cultural landmarks are shown;
 - (b) geographical place names are included only when they are required to avoid confusion or ambiguity;

- (c) shore lines, lakes, rivers and streams are shown;
- (d) relief is shown in a manner best suited to the particular elevation and obstacle characteristics of the area covered by the chart;
- (e) spot elevations are carefully selected when shown; and
- (f) figures relating to different reference levels are clearly differentiated in their presentation.

140. An aeronautical cartographic service provider shall ensure that the magnetic variation is shown

Magnetic variation.

141. An aeronautical cartographic service provider shall ensure that the –

Bearings, tracks and radials.

- (a) bearings, tracks and radials are magnetic;
- (b) bearings, tracks or radials are clearly indicated where are given with reference to True North or Grid North; and
- (c) reference grid meridian is identified when Grid North is used.

Aeronautical data

142. An aeronautical cartographic service provider shall ensure that –

Aerodromes.

- (a) all aerodromes are shown by the runway pattern;
- (b) the restrictions on the use of any landing direction is indicated;
- (c) where there is any risk of confusion between two neighbouring aerodromes, this is indicated;
- (d) abandoned aerodromes are identified as abandoned and
- (e) the aerodrome elevation is shown in a prominent position on the chart.

143. An aeronautical cartographic service provider shall ensure that the –

Obstacles.

- (a) obstacles are shown and identified;
- (b) elevation of the top of obstacles is shown to the nearest next higher metre or foot;
- (c) heights of obstacles above the aerodrome elevation are shown and

- (d) height datum is stated in a prominent position on the chart and the heights are given in parentheses on the chart, when the heights of obstacles are shown.
144. An aeronautical cartographic service provider shall ensure that the prohibited areas, restricted areas, and danger areas are depicted with their identification and vertical limits. Prohibited, restricted and danger areas
145. An aeronautical cartographic service provider shall ensure that the control zones and aerodrome traffic zones are depicted with their vertical limits and the appropriate class of airspace, where applicable. Designated airspace.
146. An aeronautical cartographic service provider shall ensure that the – Visual approach information.
- (a) visual approach procedures are shown, where applicable;
 - (b) visual aids for navigation are shown as appropriate; and
 - (c) location and type of the visual approach slope indicator systems with their nominal approach slope angle, minimum eye height over the threshold of the on-slope signal and where the axis of the system is not parallel to the runway centre line, the angle and direction of displacement, either left or right, are show
147. An aeronautical cartographic service provider shall ensure that the – Supplementary information
- (a) radio navigation aids together with their frequencies and identifications are shown as appropriate; and
 - (b) radio communication facilities with their frequencies are shown as appropriate.
- PART XIII - AERODROME/HELIPORT CHART**
148. An aeronautical cartographic service provider shall ensure that the – Function
- (a) aerodrome or heliport chart provides flight crews with information to facilitate the ground movement of aircraft –
 - (i) from the aircraft stand to the runway; and
 - (ii) from the runway to the aircraft stand; and
 - (b) aerodrome or heliport chart provides flight crews with information to facilitate the helicopter movement:
 - (i) from the helicopter stand to the touchdown and lift-off area and to the final approach and take-off area;

(ii) from the final approach and take-off area to the touchdown and lift-off area and to the helicopter stand;

(iii) along helicopter ground and air taxiways; and

(iv) along air transit routes.

(c) aerodrome or heliport chart provides essential operational information at the aerodrome or heliport.

149. An aeronautical cartographic service provider shall ensure that the – Availability.

(a) Aerodrome or Heliport Chart is made available in the manner specified in Civil Aviation (Aerodrome) Regulations for all aerodromes or heliports regularly used by international civil aviation;

(b) Aerodrome or Heliport Chart is made available in the manner specified in regulation 4(b) of these regulations.

150. An aeronautical cartographic service provider shall ensure that – Coverage and scale.

(a) the coverage and scale are sufficiently large to show clearly all the elements listed in regulation 153

(b) a linear scale is shown.

151. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the city or town or area which the aerodrome/heliport serves and the name of the aerodrome/heliport. Identification.

152. An aeronautical cartographic service provider shall ensure that the True and Magnetic North arrows and magnetic variation to the nearest degree and annual change of the magnetic variation are shown. Magnetic variation.

153. An aeronautical cartographic service provider shall ensure that – Aerodrome/heliport data.

(a) the Aerodrome or heliport chart shows:

(i) geographical coordinates in degrees, minutes and seconds for the aerodrome/heliport reference point;

(ii) elevations, to the nearest metre or foot, of the aerodrome/heliport and apron (altimeter checkpoint locations) where applicable; and for non-precision approaches, elevations and geoid

- undulations of runway thresholds and the geometric centre of the touchdown and lift-off area;
- (iii) elevations and geoid undulations, to the nearest half-metre or foot, of the precision approach runway threshold, the geometric centre of the touchdown and lift-off area, and at the highest elevation of the touchdown zone of a precision approach runway;
 - (iv) all runways including those under construction with designation number, length and width to the nearest metre, bearing strength, displaced thresholds, stopways, clearways, runway directions to the nearest degree magnetic, type of surface and runway markings;
 - (v) all aprons, with aircraft/helicopter stands, lighting, markings and other visual guidance and control aids, where applicable, including location and type of visual docking guidance systems, type of surface for heliports, and bearing strengths or aircraft type restrictions where the bearing strength is less than that of the associated runways;
 - (vi) geographical coordinates in degrees, minutes and seconds for thresholds, geometric centre of touchdown and lift-off area and/or thresholds of the final approach and take-off area (where appropriate);
 - (vii) all taxiways, helicopter air and ground taxiways with type of surface, helicopter air transit routes, with designations, width, lighting, markings (including runway-holding positions and, where established, intermediate holding positions), stop bars, other visual guidance and control aids, and bearing strength or aircraft type restrictions where the bearing strength is less than that of the associated runways;
 - (viii) where established, hot spot locations with additional cartographic properly annotated;
 - (ix) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for appropriate taxiway centre line points and aircraft stands;

- (x) where established, standard routes for taxiing aircraft with their designators;
 - (xi) the boundaries of the air traffic control service;
 - (xii) position of runway visual range observation sites;
 - (xiii) approach and runway lighting;
 - (xiv) location and type of the visual approach slope indicator systems with their nominal approach slope angle, minimum eye height over the threshold of the on-slope signal, and where the axis of the system is not parallel to the runway centre line, the angle and direction of the displacement;
 - (xv) relevant communication facilities listed with their channels and, if applicable, logon address;
 - (xvi) obstacles to taxiing;
 - (xvii) aircraft servicing areas and buildings of operational significance;
 - (xviii) VOR checkpoint and radio frequency of the aid concerned;
 - (xix) any part of the depicted movement area permanently unsuitable for aircraft, clearly identified as such;
- (b) in addition to the items in sub regulation (1) relating to heliports, the chart shall show-
- (i) heliport type;
 - (ii) touchdown and lift-off area including dimensions to the nearest metre, slope, type of surface and bearing strength in tonnes;
 - (iii) final approach and take-off area including type, true bearing to the nearest degree, designation number (where appropriate), length and width to the nearest metre, slope and type of surface;
 - (iv) safety area including length, width and type of surface;

- (v) helicopter clearway including length and ground profile;
- (vi) obstacles including type and elevation of the top of the obstacles to the nearest (next higher) metre or foot;
- (vii) visual aids for approach procedures, marking and lighting of final approach and take-off area, and of touchdown and lift-off area;
- (viii) declared distances to the nearest metre for heliports, where relevant, including:
 - (i) take-off distance available;
 - (ii) rejected take-off distance available;
 - (iii) landing distance available.

PART XIV - AERODROME GROUND MOVEMENT CHART

154. An aeronautical cartographic service provider shall ensure that the aerodrome ground movement chart provides flight crews with detailed information to facilitate the ground movement of aircraft to and from the aircraft stands and the parking or docking of aircraft. Function.

155. An aeronautical cartographic service provider shall ensure that the Aerodrome Ground Movement Chart is made available in the manner specified in regulation 4(b) where, due to congestion of information, details necessary for the ground movement of aircraft along the taxiways to and from the aircraft stands cannot be shown with sufficient clarity on the Aerodrome/Heliport Chart. Availability.

156. An aeronautical cartographic service provider shall ensure that the coverage and scale are sufficiently large to show clearly all the elements listed in regulation 159. Coverage and scale.

157. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the city or town or area which the aerodrome serves and the name of the aerodrome. Identification.

158. An aeronautical cartographic service provider shall ensure that a True North arrow is shown. Magnetic variation.

159. An aeronautical cartographic service provider shall ensure that the aerodrome ground movement chart shows in a Aerodrome data.

similar manner all the information on the Aerodrome or Heliport Chart relevant to the area depicted, including-

- (a) apron elevation to the nearest metre or foot;
- (b) aprons with aircraft stands, bearing strengths or aircraft type restrictions, lighting, marking and other visual guidance and control aids, where applicable, including location and type of visual docking guidance systems;
- (c) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for aircraft stands;
- (d) taxiways with designations, width to the nearest metre, bearing strength or aircraft type restrictions where applicable, lighting, markings (including runway-holding positions and, where established, intermediate holding positions), stop bars, and other visual guidance and control aids;
- (e) where established, hot spot locations with additional cartographic properly annotated;
- (f) where established, standard routes for taxiing aircraft, with their designators;
- (g) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for appropriate taxiway centre line points;
- (h) the boundaries of the air traffic control service;
- (i) relevant communication facilities listed with their channels and, if applicable, logon address;
- (j) obstacles to taxiing;
- (k) aircraft servicing areas and buildings of operational significance;
- (l) VOR checkpoint and radio frequency of the aid concerned;
- (m) any part of the depicted movement area permanently unsuitable for aircraft, clearly identified as such.

PART XV - AIRCRAFT PARKING/DOCKING CHART —
ICAO

160. An aeronautical cartographic service provider shall ensure that the aircraft parking chart provides flight crews with

Function.

detailed information to facilitate the ground movement of aircraft between the taxiways and the aircraft stands and the parking/docking of aircraft.

161. An aeronautical cartographic service provider shall ensure that the Aircraft Parking/Docking Chart is made available in the manner prescribed regulation 4(b) where, due to the complexity of the terminal facilities, the information cannot be shown with sufficient clarity on the Aerodrome/Heliport Chart or on the Aerodrome Ground Movement Chart.

Availability

162. An aeronautical cartographic service provider shall ensure that the coverage and scale shall be sufficiently large to show clearly all the elements listed in regulation 165.

Coverage and scale

163. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the city or town or area which the aerodrome serves and the name of the aerodrome.

Identification.

164. An aeronautical cartographic service provider shall ensure that a True North arrow is shown.

Magnetic variation

165. An aeronautical cartographic service provider shall ensure that the chart shows in a similar manner all the information on the Aerodrome/Heliport Chart and the Aerodrome Ground Movement Chart relevant to the area depicted, including-

Aerodrome data

- (a) apron elevation to the nearest metre or foot;
- (b) aprons with aircraft stands, bearing strengths or aircraft type restrictions, lighting, marking and other visual guidance and control aids, where applicable, including location and type of visual docking guidance systems;
- (c) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for aircraft stands;
- (d) taxiway entries with designations, including runway-holding positions and, where established, intermediate holding positions, and stop bars;
- (e) where established, hot spot locations with additional information properly annotated;
- (f) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for appropriate taxiway centre line points;
- (g) the boundaries of the air traffic control service;

- (h) relevant communication facilities listed with their channels and, if applicable, logon address;
- (i) obstacles to taxiing;
- (j) aircraft servicing areas and buildings of operational significance;
- (k) VOR checkpoint and radio frequency of the aid concerned;
- (l) any part of the depicted movement area permanently unsuitable for aircraft, clearly identified as such.

PART XVI -WORLD AERONAUTICAL CHART —
ICAO 1:1 000 000

166. An aeronautical cartographic service provider shall ensure that the World Aeronautical chart – 1:1,000,000 provides information to satisfy the requirements of visual air navigation – Function.

- (a) as a basic aeronautical chart:
 - (i) when highly specialized charts lacking visual information do not provide essential data;
 - (ii) to provide complete world coverage at a constant scale with a uniform presentation of planimetric data;
 - (iii) in the production of other charts required by international civil aviation;
- (b) as a pre-flight planning chart.

167. An aeronautical cartographic service provider shall ensure that the – Availability.

- (a) World Aeronautical Chart 1:1 000 000 is made available in the manner specified in regulation 4(b) for all areas delineated in fifth Schedule;
- (b) selection of a scale of other than 1:1 000 000 is determined by regional agreement to ensure complete coverage of all land areas and adequate continuity in any one coordinated series.

168. An aeronautical cartographic service provider shall ensure that – Scale.

- (a) the linear scales for kilometres and nautical miles arranged with their zero points in the same vertical line is shown in the margin in the following order-

- (i) kilometres
- (ii) nautical miles,
- (b) the length of the linear scales represent at least 200 km (110 NM); and
- (c) a conversion scale in metre or feet is shown in the margin.

169. An aeronautical cartographic service provider shall ensure that – Format.

- (a) the title and marginal notes are in English;
- (b) the information regarding the number of the adjoining sheets and the unit of measurement to express elevations is located as to be clearly visible when the sheet is folded;
- (c) the sheet lines conform with those shown in the index in fifth Schedule, whenever practicable;
- (d) the sheet lines used are notified to the International Civil Aviation Organization for publication in the International Civil Aviation Organization's Aeronautical Chart Catalogue;
- (e) overlaps are provided by extending the chart area on the top and right side beyond the area given on the index;
- (f) the overlap area contain all aeronautical, topographical, hydrographical and cultural information; and
- (g) the overlap extend up to 28 km (15 NM), if possible, but in any case from the limiting parallels and meridians of each chart to the neat line.

170. (1) An aeronautical cartographic service provider shall ensure that the projection is the Lambert conformal conic projection, in separate bands for each tier of charts and the standard parallels for each 4° band is 40 ' south of the northern parallel and 40 ' north of the southern parallel. Projection.

(2) The graticules and graduations are shown as follows:

(a) Parallels:

Latitude	Distance between Parallels	Graduation on Parallels
0 to 72 ⁰	30'	1'
72 ⁰ to 84 ⁰	30'	5'
84 ⁰ to 89 ⁰	30'	'
89 ⁰ to 90 ⁰	30'	5' (only on degree parallels from 720 to 890)

(b) Meridians:

Latitude	Distance between Parallels	Graduation on Parallels
0 to 52 ⁰	30'	1'
52 ⁰ to 72 ⁰	30'	1' (Only on even numbered meridians)
72 ⁰ to 84 ⁰	10'	1'
84 ⁰ to 89 ⁰	50'	1'
89 ⁰ to 90 ⁰	150'	1' (Only on every fourth meridian)

- (c) the graduation marks at 1' and 5' intervals extend away from the Greenwich Meridian and from the Equator and each 10' interval is shown by a mark on both sides of the graticule line;
- (d) the length of the graduation marks are approximately 1.3 mm (0.05 in) for the 1' intervals, and 2 mm (0.08 in) for the 5' intervals and 2 mm (0.08 in) extending on both sides of the graticule line for the 10' intervals;
- (e) all meridians and parallels shown are numbered in the borders of the chart;
- (f) each parallel is numbered within the body of the chart in such a manner that the parallel can be readily identified when the chart is folded; and
- (g) the name and basic parameters of the projection are indicated in the margin.

171. An aeronautical cartographic service provider shall ensure that sheet numbering is in conformity with the index in fifth Schedule. Identification.
- Culture and topography*
172. An aeronautical cartographic service provider shall ensure that the cities, towns and villages are selected and shown according to their relative importance to visual air navigation. Built-up areas.
173. An aeronautical cartographic service provider shall ensure that – Railroads.
- (a) all railroads having landmark value are shown and named where space permits;
- (b) the important tunnels are shown.
174. An aeronautical cartographic service provider shall ensure that the – Highways and roads.
- (a) road systems are shown in sufficient detail to indicate significant patterns from the air; and
- (b) roads are not be shown in built-up areas unless they can be distinguished from the air as definite landmarks.
175. An aeronautical cartographic service provider shall ensure that the natural and cultural landmarks, such as bridges, prominent transmission lines, permanent cable car installations, wind turbines, mine structures, forts, ruins, levees, pipelines, rocks, bluffs, cliffs, sand dunes, isolated lighthouses and lightships, when considered to be of importance for visual air navigation, are shown. Landmarks.
176. An aeronautical cartographic service provider shall ensure that international boundaries are shown and undemarcated and undefined boundaries are distinguished by descriptive notes. Political boundaries.
177. An aeronautical cartographic service provider shall ensure that all water features compatible with the scale of the chart comprising shore lines, lakes, rivers and streams including those non-perennial in nature, salt lakes, glaciers and ice caps are shown. Hydrography.
178. An aeronautical cartographic service provider shall ensure that the – Contours.
- (a) contours are shown and the selection of intervals is governed by the requirement to depict clearly the relief features required in air navigation; and
- (b) values of the contours used are shown.

179. An aeronautical cartographic service provider shall ensure that the – Hypsometric tints.
- (a) range of elevations for the tints is shown when hypsometric tints are used;
 - (b) scale of the hypsometric tints used on the chart is shown in the margin.
180. An aeronautical cartographic service provider shall ensure that the – Spot elevations.
- (a) spot elevations are shown at selected critical points and the elevations selected are the highest in the immediate vicinity and indicate the top of a peak and ridge;
 - (b) elevations in valleys and at lake surface level which are of special value to the aviator are shown and the position of each selected elevation is indicated by a dot;
 - (c) elevation of the highest point on the chart and its geographical position to the nearest five minutes are indicated in the margin; and
 - (d) spot elevation of the highest point in any sheet is cleared of hypsometric tinting.
181. An aeronautical cartographic service provider shall ensure that the – Incomplete or unreliable relief.
- (a) areas that have not been surveyed for contour information are labelled “Relief data incomplete”;
 - (b) charts on which spot elevations are generally unreliable bear a warning note prominently displayed on the face of the chart in the colour used for aeronautical information, as follows: “Warning — The reliability of relief cartographic on this chart is doubtful and elevations are used with caution.”
182. An aeronautical cartographic service provider shall ensure that escarpments are shown when they are prominent landmarks or when cultural detail is very sparse. Escarpments.
183. An aeronautical cartographic service provider shall ensure that – Wooded areas.
- (a) wooded areas are shown; and
 - (b) the approximate extreme northern or southern limits of tree growth are indicated by a dashed black line where shown and are appropriately labelled.

184. An aeronautical cartographic service provider shall ensure that the date of latest information shown on the topographic base is indicated in the margin. Date of topographic information.
185. An aeronautical cartographic service provider shall ensure that the – Magnetic variation.
- (a) isogonic lines are shown; and
 - (b) date of the isogonic information is indicated in the margin.
- Aeronautical data*
186. An aeronautical cartographic service provider shall ensure that An aeronautical data shown are kept to a minimum consistent with the use of the chart for visual navigation and the revision cycle. General.
187. An aeronautical cartographic service provider shall ensure that the – Aerodromes.
- (a) land and water aerodromes and heliports are shown with their names, to the extent that they do not produce undesirable congestion on the chart, priority being given to those of greatest aeronautical significance;
 - (b) aerodrome elevation, the lighting available, the type of runway surface and the length of the longest runway or channel, shown in abbreviated form for each aerodrome in conformity with the example in second schedule, is indicated provided they do not cause undesirable clutter on the chart; and
 - (c) abandoned aerodromes which are still recognizable as aerodromes from the air are shown and identified as abandoned.
188. An aeronautical cartographic service provider shall ensure that the – Obstacles.
- (a) obstacles are shown; and
 - (b) prominent transmission lines, permanent cable car installations and wind turbines, which are obstacles, are shown when considered of importance to visual flight.
189. An aeronautical cartographic service provider shall ensure that the prohibited, restricted and danger areas are shown. Prohibited, restricted and danger areas.
190. An aeronautical cartographic service provider shall ensure that – Air traffic services system.
- (a) significant elements of the air traffic services system including, where practicable, control zones, aerodrome

traffic zones, control areas, flight information regions and other airspaces in which VFR flights operate are shown together with the appropriate class of airspace; and

- (b) the air defense identification zone are shown where appropriate and properly identified

191. An aeronautical cartographic service provider shall ensure that radio navigation aids are shown by the appropriate symbol and named, but excluding their frequencies, coded designators, times of operation and other characteristics unless any or all of the information shown is kept up to date by means of new editions of the chart.

Radio navigation aids.

192. An aeronautical cartographic service provider shall ensure that the –

Supplementary information.

- (a) aeronautical ground lights together with their characteristics or their identifications or both are shown;
- (b) the marine lights on outer prominent coastal or isolated features of not less than 28 km (15 NM) visibility range are shown where they are:
- (i) not less distinguishable than more powerful marine lights in the vicinity;
- (ii) readily distinguishable from other marine or other types of lights in the vicinity of built-up coastal areas and
- (iii) the only lights of significance available.

PART XVII – AERONAUTICAL CHART — ICAO 1:500 000

193. An aeronautical cartographic service provider shall ensure that the aeronautical chart - 1: 500,000 provides information to satisfy the requirements of visual air navigation for low speed, short- or medium-range operations at low and intermediate altitudes.

Function.

194. An aeronautical cartographic service provider shall ensure that the Aeronautical Chart 1:500 000 is made available in the manner specified in regulation 4(2) for all areas delineated in fifth Schedule.

Availability

195. An aeronautical cartographic service provider shall ensure that –

Scales.

- (a) the linear scales for kilometres and nautical miles arranged in the following order:

- (i) kilometres,
 - (ii) nautical miles, with their zero points in the same vertical line is shown in the margin; and
- (b) a conversion scale is shown in the margin.

196. An aeronautical cartographic service provider shall ensure that the – Format

- (a) title and marginal notes is in English;
- (b) information regarding the number of the adjoining sheets and the unit of measurement used to express elevation is located as to be clearly visible when the sheet is folded;
- (c) sheets are quarter sheets of the World Aeronautical Chart 1:1 000 000 whenever practicable;
- (d) an appropriate index to adjacent sheets, showing the relationship between the two chart series is included on the face of the chart or on the reverse side;
- (e) overlaps are provided by extending the chart area on the top and right side beyond the area given on the index;
- (f) overlap area in paragraph (e) contain all aeronautical, topographical, hydrographical and cultural information; and
- (g) overlap extend up to 15 km (8 NM), if possible, but in any case from the limiting parallels and meridians of each chart to the neat line.

197. An aeronautical cartographic service provider shall ensure that – Projection

- (a) a conformal projection is used;
- (b) the Parallels are shown at intervals of 30';
- (c) the meridians are shown at intervals of 30 ';
- (d) the graduation marks are shown at 1 ' intervals along each whole degree meridian and parallel, extending away from the Greenwich Meridian and from the Equator and each 10 ' interval is shown by a mark on both sides of the graticule line;

- (e) the meridians and parallels shown are numbered in the borders of the chart; and
- (f) the name and basic parameters of the projection is indicated in the margin.

198. An aeronautical cartographic service provider shall ensure that – Identification.

- (a) each sheet is identified by a name of the principal town or of a main geographical feature appearing on the sheet;
- (b) the sheets are identified by the reference number of the corresponding World Aeronautical Chart —1:1 000 000 where applicable, with the addition of one or more of the following letter suffixes indicating the quadrant or quadrants:

Letter	Chart quadrant
A	North-West
B	North-East
C	South-East
D	South-West

Culture and topography

199. An aeronautical cartographic service provider shall ensure that the cities, towns and villages are selected and shown according to their relative importance to visual air navigation. Built-up areas.

200. An aeronautical cartographic service provider shall ensure that – Railroads.

- (a) all railroads having landmark value are shown; and
- (b) the tunnels are shown when they serve as prominent landmarks.

201. An aeronautical cartographic service provider shall ensure that the – Highways and roads.

- (a) road systems are shown in sufficient detail to indicate significant patterns from the air; and
- (b) roads not are shown in built-up areas unless they can be distinguished from the air as definite landmarks.

202. An aeronautical cartographic service provider shall ensure that the natural and cultural landmarks, such as bridges, prominent transmission lines, permanent cable car installations, Landmarks.

wind turbines, mine structures, lookout towers, forts, ruins, levees, pipelines, rocks, bluffs, cliffs, sand dunes, isolated lighthouses and lightships are shown when considered to be of importance for visual air navigation.

203. An aeronautical cartographic service provider shall ensure that the international boundaries are shown and undemarcated and undefined boundaries are distinguished by descriptive notes. Political boundaries.

204. An aeronautical cartographic service provider shall ensure that all water features compatible with the scale of the chart comprising shore lines, lakes, rivers and streams including those non-perennial in nature, salt lakes, glaciers and ice caps are shown. Hydrography.

205. An aeronautical cartographic service provider shall ensure that – Contours.

- (a) the Contours are shown and the selection of intervals shall be governed by the requirement to depict clearly the relief features required in air navigation and
- (b) the values of the contours used are shown.

206. An aeronautical cartographic service provider shall ensure that – Hypsometric tints.

- (a) the range of elevations for the tints is shown when hypsometric tints are used; and
- (b) the scale of the hypsometric tints used on the chart are shown in the margin.

207. An aeronautical cartographic service provider shall ensure that – Spot elevations.

- (a) the spot elevations are shown at selected critical points.
- (b) the elevations selected are the highest in the immediate vicinity and indicate the top of a peak and ridge;
- (c) the elevations in valleys and at lake surface levels which are of navigational value are shown and the position of each selected elevation shall be indicated by a dot;
- (d) the elevation of the highest point on the chart and its geographical position to the nearest five minutes is indicated in the margin; and
- (e) the spot elevation of the highest point on any sheet is cleared of hypsometric tinting.

208. An aeronautical cartographic service provider shall ensure that – Incomplete or unreliable relief.

- (a) the areas that have not been surveyed for contour cartographic are labelled “Relief data incomplete”; and
- (b) the charts on which spot elevations are unreliable bear a warning note prominently displayed on the face of the chart in the colour used for aeronautical cartographic, as follows:
 “Warning — the reliability of relief cartographic on this chart is doubtful and elevations shall be used with caution.”

209. An aeronautical cartographic service provider shall ensure that the escarpments are shown when they are prominent landmarks or when cultural detail is very sparse. Escarpments.

210. An aeronautical cartographic service provider shall ensure that when the wooded areas are shown the approximate northern or southern limits of tree growth shall be indicated by a dashed black line where shown, and are appropriately labelled. Wooded areas.

211. An aeronautical cartographic service provider shall ensure that the date of latest information shown on the topographic base is indicated in the margin. Date of topographic information.

212. An aeronautical cartographic service provider shall ensure that – Magnetic variation.

- (a) the isogonic lines are shown and
- (b) the date of the isogonic cartographic is indicated in the margin.

Aeronautical data

213. An aeronautical cartographic service provider shall ensure that the aeronautical information is shown consistent with the use of the chart and the revision cycle. General information.

214. An aeronautical cartographic service provider shall ensure that the – Aerodromes.

- (a) land and water aerodromes and heliports are shown with their names, to the extent that they do not produce undesirable congestion on the chart, priority being given to those of greatest aeronautical significance;
- (b) aerodrome elevation, the lighting available, the type of runway surface and the length of the longest runway or channel, shown in abbreviated form for each

aerodrome in conformity with the example in second schedule, provided they do not cause undesirable clutter on the chart, are indicated; and

- (c) abandoned aerodromes which are still recognizable as aerodromes from the air are shown and identified as abandoned.

215. An aeronautical cartographic service provider shall ensure that the –

Obstacles.

- (a) obstacles are shown; and
- (b) prominent transmission lines, permanent cable car installations and wind turbines, which are obstacles are shown when considered of importance to visual flight.

216. An aeronautical cartographic service provider shall ensure that the prohibited, restricted and danger areas are shown.

Prohibited, restricted and danger areas.

217. An aeronautical cartographic service provider shall ensure that the –

Air traffic services system.

- (a) significant elements of the air traffic services system including, control zones, aerodrome traffic zones, control areas, flight cartographic regions and other airspaces in which VFR flights operate are shown together with the appropriate class of airspace, where practicable; and
- (b) air defence identification zone are shown and properly identified where appropriate.

218. An aeronautical cartographic service provider shall ensure that the radio navigation aids are shown by the appropriate symbol and named, but excluding their frequencies, coded designators, times of operation and other characteristics unless any or all of this information shown is kept up to date by means of new editions of the chart.

Radio navigation aids.

219. An aeronautical cartographic service provider shall ensure that the –

Supplementary information.

- (a) aeronautical ground lights together with their characteristics or their identifications or both are shown and
- (b) marine lights on outer prominent coastal or isolated features of not less than 28 km (15 NM) visibility range are shown where they are:
 - (i) not less distinguishable than more powerful marine lights in the vicinity;

(ii) readily distinguishable from other marine or other types of lights in the vicinity of built-up coastal areas;

(iii) the only lights of significance available.

PART XVIII - AERONAUTICAL NAVIGATION CHART -
SMALL SCALE

220. An aeronautical cartographic service provider shall ensure that the aeronautical navigation chart – small scale –

Function.

- (a) serves as an air navigation aid for flight crews of long-range aircraft at high altitudes;
- (b) provides selective checkpoints over extensive ranges for identification at high altitudes and speeds, which are required for visual confirmation of position;
- (c) provides for continuous visual reference to the ground during long-range flights over areas lacking radio or other electronic navigation aids, or over areas where visual navigation is preferred or becomes necessary;
- (d) provides a general purpose chart series for long-range flight planning and plotting.

221. An aeronautical cartographic service provider shall ensure that the Aeronautical Navigation Chart — Small Scale is made available in the manner specified in regulation 4(b) for all areas delineated in fifth schedule.

Availability.

222. An aeronautical cartographic service provider shall ensure that the –

Coverage and scale.

- (a) the scale is in the range of 1:2 000 000 to 1:5 000 000;
- (b) the scale of the chart is substituted in the title for the words “Small Scale”;
- (c) the Linear scales for kilometres and nautical miles arranged in the following order-
 - (i) kilometers,
 - (ii) nautical miles, with their zero points in the same vertical line are shown in the margin; and
- (d) a conversion scale in metre or feet is shown in the margin.

223. An aeronautical cartographic service provider shall ensure that the –

Format.

- (a) title and marginal notes are in English; and
- (b) information regarding the number of the adjoining sheets and the unit of measurement to express elevations is located as to be clearly visible when the sheet is folded.
224. An aeronautical cartographic service provider shall ensure that – Projection
- (a) a conformal projection is used;
- (b) the name and basic parameters of the projection is shown in the margin;
- (c) the parallels are shown at intervals of 1°;
- (d) the graduations on the parallels are shown at sufficiently close intervals compatible with the latitude and the scale of the chart;
- (e) meridians are shown at intervals compatible with the latitude and the scale of the chart.
- (f) the graduations on the meridians are shown at intervals not exceeding 5' ;
- (g) the graduation marks extend away from the Greenwich Meridian and from the Equator;
- (h) all meridians and parallels shown are numbered in the borders of the chart; and
- (i) in addition, when required, meridians and parallels are numbered within the body of the chart in such a manner that they can be readily identified when the chart is folded.
- Culture and topography*
225. An aeronautical cartographic service provider shall ensure that the cities, towns and villages are selected and shown according to their relative importance to visual air navigation. Built-up areas
226. An aeronautical cartographic service provider shall ensure that all railroads having landmark value are shown. Railroads
227. An aeronautical cartographic service provider shall ensure that the road systems are shown in sufficient detail to indicate significant patterns from the air. Highways and roads
228. An aeronautical cartographic service provider shall ensure that the international boundaries are shown and the Political boundaries

undemarcated including undefined boundaries are distinguished by descriptive notes.

229. An aeronautical cartographic service provider shall ensure that all water features compatible with the scale of the chart comprising shore lines, lakes, rivers and streams including those non-perennial in nature, salt lakes, glaciers and ice caps are shown. Hydrography.

230. An aeronautical cartographic service provider shall ensure that the – Contours.

- (a) contours are shown and the selection of intervals are governed by the requirement to depict clearly the relief features required in air navigation; and
- (b) values of the contours used are shown.

231. An aeronautical cartographic service provider shall ensure that the – Hypsometric tints.

- (a) range of elevations for the tints are shown when hypsometric tints are used;
- (b) scale of the hypsometric tints used on the chart is shown in the margin.

232. An aeronautical cartographic service provider shall ensure that the – Spot elevations.

- (a) spot elevations are shown at selected critical points;
- (b) elevations selected are the highest in the immediate vicinity and indicate the top of a peak or ridge;
- (c) elevations in valleys and at lake surface levels which are of value to visual air navigation are shown and the position of each selected elevation are indicated by a dot; and
- (d) elevation of the highest point on the chart and its geographical position to the nearest five minutes is indicated in the margin.

233. An aeronautical cartographic service provider shall ensure that the – Incomplete or unreliable relief.

- (a) areas that have not been surveyed for contour information are labelled "Relief data incomplete".
- (b) charts on which spot elevations are unreliable bear a warning note prominently displayed on the face of the chart in the colour used for aeronautical information, as follows:

“Warning — the reliability of relief cartographic on this chart is doubtful and elevations shall be used with caution.”

234. An aeronautical cartographic service provider shall ensure that the date of latest information shown on the topographic base is indicated in the margin

Date of topographic information

235. An aeronautical cartographic service provider shall ensure that the –

Colours

- (a) the subdued colours are used for the chart background to facilitate plotting and
- (b) good colour contrast is ensured to emphasize features important to visual air navigation.

236. An aeronautical cartographic service provider shall ensure that the –

Magnetic variation

- (a) isogonic lines are shown and
- (b) date of isogonic cartographic shall be indicated in the margin.

Aeronautical data

237. An aeronautical cartographic service provider shall ensure that the land and water aerodromes and heliports are shown with their names, to the extent that they do not produce undesirable congestion on the chart, priority being given to those of greatest aeronautical significance.

Aerodromes

238. An aeronautical cartographic service provider shall ensure that the obstacles are shown.

Obstacles

239. An aeronautical cartographic service provider shall ensure that the prohibited, restricted and danger areas are shown when considered to be of importance to air navigation.

Prohibited, restricted and danger areas

240. An aeronautical cartographic service provider shall ensure that the –

Air traffic services system

- (a) significant elements of the air traffic services system are shown when considered to be of importance to air navigation; and
- (b) air defence identification zone are shown and properly identified where appropriate.

PART XIX - PLOTTING CHART — ICAO

241. An aeronautical cartographic service provider shall ensure that the plotting chart provides a means of maintaining a continuous flight record of the aircraft position by various fixing methods and dead reckoning in order to maintain an intended flight path.

Function

242. An aeronautical cartographic service provider shall ensure that the plotting chart is made available, in the manner prescribed in regulation 4(b) to cover major air routes over oceanic areas and sparsely settled areas used by international civil aviation. Availability.
243. An aeronautical cartographic service provider shall ensure that the – Coverage and scale.
- (a) chart for a particular region covers major air routes and their terminals on a single sheet, where practicable;
 - (b) scale is governed by the area to be covered.
244. An aeronautical cartographic service provider shall ensure that the sheet is of a size that can be adapted for use on a navigator's plotting table. Format.
245. An aeronautical cartographic service provider shall ensure that – Projection.
- (a) the parallels and meridians are shown;
 - (b) the graduation marks are shown at consistent intervals along an appropriate number of parallels and meridians and the interval selected, regardless of scale, minimizes the amount of interpolation required for accurate plotting; and
 - (c) If a navigational grid is shown on charts covering the higher latitudes, it shall comprise lines parallel to the Meridian or anti-Meridian of Greenwich.
246. An aeronautical cartographic service provider shall ensure that each sheet is identified by chart series and number. Identification.
247. An aeronautical cartographic service provider shall ensure that the – Culture and topography.
- (a) generalized shore lines of all open water areas, large lakes and rivers are shown;
 - (b) spot elevations for selected features constituting a hazard to air navigation are shown;
 - (c) particularly hazardous or prominent relief features are emphasized.
248. An aeronautical cartographic service provider shall ensure that the – Magnetic variation.

- (a) isogonals are shown at consistent intervals throughout the chart and the interval selected, regardless of scale, minimizes the amount of interpolation required;
- (b) date of the isogonic information is shown.

249. An aeronautical cartographic service provider shall ensure that the – Aeronautical data.

- (a) the following aeronautical data are shown –
 - (i) aerodromes regularly used by international commercial air transport together with their names;
 - (ii) selected radio aids to navigation that will contribute to position-finding together with their names and identifications;
 - (iii) lattices of long-range electronic aids to navigation, as required;
 - (iv) boundaries of flight cartographic regions, control areas and control zones necessary to the function of the chart;
 - (v) designated reporting points necessary to the function of the chart;
 - (vi) ocean station vessels;
- (b) aeronautical ground lights and marine lights useful for air navigation are shown where other means of navigation are non-existent.

PART XX - ELECTRONIC AERONAUTICAL CHART DISPLAY — ICAO

250. An aeronautical cartographic service provider shall ensure that the Electronic Aeronautical Chart Display with adequate back-up arrangements and in compliance with the requirements of Civil Aviation (Operations of aircraft) Regulations for charts, enables flight crews to execute, in a convenient and timely manner, route planning, route monitoring and navigation by displaying the required information. Function.

251. An aeronautical cartographic service provider shall ensure that the Electronic Aeronautical Chart Display is capable of displaying all aeronautical, cultural and topographic information required by part V and part VII through to part XIX. Information available for display.

Display requirements

252. An aeronautical cartographic service provider shall ensure that the – Display categories.

- (a) information available for display is subdivided into the following categories-
 - (i) basic display information, permanently retained on the display and consisting of the minimum information essential for the safe conduct of flight; and
 - (ii) other display information, which may be removed from the display or displayed individually on demand, and consisting of information not considered essential for the safe conduct of flight.
- (b) adding or removing other display information is a simple function but is not possible to remove information contained in the basic display.

253. An aeronautical cartographic service provider shall ensure that the –

Display mode and generation of neighbouring area.

- (a) the Electronic Aeronautical Chart Display is capable of continuously plotting the aircraft's position in a true motion mode where reset and generation of the surrounding area takes place automatically.
- (b) it is possible manually to change the chart area and the position of the aircraft relative to the edge of the display.

254. An aeronautical cartographic service provider shall ensure that it is possible to vary the scale at which a chart is displayed.

Scale.

255. An aeronautical cartographic service provider shall ensure that –

Symbols.

- (a) the symbols used conform to those specified for electronic charts in the second schedule – International Civil Aviation Organization Chart Symbols except where it is desired to show items for which no International Civil Aviation Organization chart symbol is provided;
- (b) in cases where no International Civil Aviation Organization chart symbols are provided, electronic chart symbols are chosen which-
 - (i) employ a minimum use of lines, arcs and area fills;
 - (ii) do not cause confusion with any existing aeronautical chart symbol;

(iii) do not impair the legibility of the display.

256. An aeronautical cartographic service provider shall ensure that the – Display hardware.

- (a) effective size of the chart presentation is sufficient to display the information required by regulation 252 without excessive scrolling;
- (b) display has the capabilities required to accurately portray required elements of second schedule — International Civil Aviation Organization Chart Symbols;
- (c) method of presentation ensures that the displayed information is clearly visible to the observer in the conditions of natural and artificial light experienced in the cockpit; and
- (d) display luminance is adjustable by the flight crew.

257. An aeronautical cartographic service provider shall ensure that – Provision and updating of data.

- (a) the provision and updating of data for use by the display is in conformance with the aeronautical data quality system requirements;
- (b) the display is capable of automatically accepting authorized updates to existing data and means of ensuring that authorized data and all relevant updates to that data have been correctly loaded into the display is provided;
- (c) the display is capable of accepting updates to authorized data entered manually with simple means for verification prior to final acceptance of the data and updates entered manually are distinguishable on the display from authorized data and its authorized updates and shall not affect display legibility;
- (d) a record is kept of all updates, including date and time of application;
- (e) the display allows the flight crew to display updates so that the flight crew may review the contents of the updates and determine that they have been included in the system.

258. An aeronautical cartographic service provider shall ensure that the – Performance tests, malfunction alarms and indications.

- (a) a means is provided for carrying out on-board tests of

major functions and in case of a failure, the test displays information to indicate which part of the system is at fault.

- (b) a suitable alarm or indication of system malfunction is provided.

259. An aeronautical cartographic service provider shall ensure that to ensure safe navigation in case of a failure of the Electronic Aeronautical Chart Display the provision of adequate back-up arrangements include-

Back-up arrangements.

- (a) facilities enabling a safe takeover of display functions in order to ensure that a failure does not result in a critical situation; and
- (b) a back-up arrangement facilitating the means for safe navigation of the remaining part of the flight.

PART XXI - AIR TRAFFIC CONTROL SURVEILLANCE
MINIMUM ALTITUDE CHART — ICAO

260. An aeronautical cartographic service provider shall ensure that -

Function.

- (a) the Air Traffic Control Surveillance Minimum Altitude chart provides information that will enable flight crews to monitor and cross-check altitudes assigned by a controller using an air traffic services surveillance system;
- (b) a note indicating that the chart may only be used for cross-checking of altitudes assigned while the aircraft is identified is prominently displayed on the face of the chart.

261. An aeronautical cartographic service provider shall ensure that the Air Traffic Control Surveillance Minimum Altitude Chart is made available, in the manner prescribed in regulation 4(b) where vectoring procedures are established and minimum vectoring altitudes cannot be shown adequately on the Area Chart, Standard Departure Chart — Instrument or Standard Arrival Chart — Instrument.

Availability.

262. An aeronautical cartographic service provider shall ensure that the -

Coverage and scale.

- (a) coverage of the chart is sufficient to effectively show the information associated with vectoring procedures; and
- (b) chart is drawn to scale.

263. An aeronautical cartographic service provider shall ensure that –
- Projection.
- (a) a conformal projection on which a straight line approximates a geodesic line is used;
 - (b) the graduation marks are placed at consistent intervals along the neat lines, as appropriate.
264. An aeronautical cartographic service provider shall ensure that the chart is identified by the name of the aerodrome for which the vectoring procedures are established or, when procedures apply to more than one aerodrome, the name associated with the airspace portrayed.
- Identification.
265. An aeronautical cartographic service provider shall ensure that the –
- Culture and topography.
- (a) generalized shorelines of all open water areas, large lakes and rivers are shown except where they conflict with data more applicable to the function of the chart;
 - (b) appropriate spot elevations and obstacles are shown.
266. An aeronautical cartographic service provider shall ensure that the average magnetic variation of the area covered by the chart is shown to the nearest degree.
- Magnetic variation.
267. An aeronautical cartographic service provider shall ensure that –
- Bearings, tracks and radials.
- (a) the Bearings, tracks and radials are magnetic;
 - (b) Where bearings, tracks or radials are given with reference to True North or Grid North, the reference is clearly indicated and where Grid North is used, its reference grid meridian is identified.
- Aeronautical data*
268. An aeronautical cartographic service provider shall ensure that –
- Aerodromes.
- (a) all aerodromes that affect the terminal routings are shown and where appropriate, a runway pattern symbol is used;
 - (b) the elevation of the primary aerodrome to the nearest metre or foot is shown.
269. An aeronautical cartographic service provider shall ensure that the prohibited, restricted and danger areas are depicted with their identification.
- Prohibited, restricted and danger areas.

270. An aeronautical cartographic service provider shall ensure that the chart shows components of the established air traffic services system including-

Air traffic services system.

- (a) relevant radio navigation aids together with their identifications;
- (b) lateral limits of relevant designated airspace;
- (c) relevant significant points associated with standard instrument departure and arrival procedures;
- (d) transition altitude, where established;
- (e) information associated with vectoring including-
 - (i) minimum vectoring altitudes to the nearest higher 50 m or 100 ft, clearly identified;
 - (ii) lateral limits of minimum vectoring altitude sectors normally defined by bearings and radials to/from radio navigation aids to the nearest degree or, if not practicable, geographical coordinates in degrees, minutes and seconds and shown by heavy lines so as to clearly differentiate between established sectors;
 - (iii) distance circles at 20-km or 10-NM intervals or, when practicable, 10-km or 5-NM intervals shown as fine dashed lines with the radius indicated on the circumference and centred on the identified aerodrome main VOR radio navigation aid or, if not available, on the aerodrome/heliport reference point;
 - (iv) notes concerning correction for low temperature effect, as applicable; and
 - (v) communications procedures including call sign(s) and channel(s) of the Air Traffic Control unit(s) concerned.

271. (1) A license or any other document issued to an operator prior to the commencement of these Regulations shall continue to be in force as if it was issued under these Regulations until it expires or is cancelled by the Authority.

Transition provisions.


(2) Notwithstanding any other provision of these Regulations, a person who at the commencement of these Regulations, is carrying out any acts, duties or operations affected

by these Regulations shall, within one (1) year from the date of commencement, or within such longer time that the Cabinet Secretary may, by notice in the Gazette prescribe, comply with the requirements of these Regulations or cease to carry out such acts, duties or operations.

FIRST SCHEDULE

(r.7)

MARGINAL LAYOUT



SECOND SCHEDULE
ICAO CHART SYMBOLS

(r. xxxxxxx)

1. CATEGORY INDEX

	<i>Symbol No.</i>
TOPOGRAPHY (1-18)	
Approximate contours	2
Areas not surveyed for contour information or relief data incomplete	18
Bluff, cliff or escarpment	4
Coniferous trees	15
Contours	1
Gravel	8
Highest elevation on chart	12
Lava flow	5
Levee or esker	9
Mountain pass	11
Other trees	16
Palms	17
Relief shown by hachures	3
Sand area	7
Sand dunes	6
Spot elevation (of doubtful accuracy)	14
Spot elevation	13
Unusual land features appropriately labelled	10
 HYDROGRAPHY (19-46)	
Abandoned canal	30
Canal	29
Charted isolated rock	44
Coral reefs and ledges	22
Danger line (2 m or one fathom line)	43
Dry lake bed	39
Falls	28
Glaciers and ice caps	42
Lakes (non-perennial)	32
Lakes (perennial)	31
Large river (perennial)	23
Rapids	27
Reservoir	38
Rice field	36
Rivers and streams (non-perennial)	25
Rivers and streams (unsurveyed)	26
Rock awash	45
Salt lake	33
Salt pans (evaporator)	34

	<i>Symbol No.</i>
Shoals	41
Shore line (reliable)	19
Shore line (unreliable)	20
Small river (perennial)	24
Spring, well or water hole	37
Swamp	35
Tidal flats	21
Unusual water features appropriately labelled	46
Wash	40
CULTURE (47-83)	
<i>Built-up Areas (47-50)</i>	
Buildings	50
City or large town	47
Town	48
Village	49
<i>Railroads (51-56)</i>	
Railroad (single track)	51
Railroad (two or more tracks)	52
Railroad (under construction)	53
Railroad bridge	54
Railroad station	56
Railroad tunnel	55
<i>Highways and Roads (57-62)</i>	
Dual highway	57
Primary road	58
Road bridge	61
Road tunnel	62
Secondary road	59
Trail	60
<i>Miscellaneous (63-83)</i>	
Boundaries (international)	63
Church	80
Coast guard station	73
Dam	67
Fence	65
Ferry	68
Forest ranger station	76
Fort	79
Lookout tower	74
Mine	75
Mosque	81
Nuclear power station	72
Oil or gas field	70
Outer boundaries	64
Pagoda	82

	<i>Symbol No.</i>
Pipeline.....	69
Race track or stadium.....	77
Ruins.....	78
Tank farms.....	71
Telegraph or telephone line (when a landmark).....	66
Temple.....	83
AERODROMES (84-95)	
Abandoned or closed aerodrome.....	91
Aerodrome for use on charts on which aerodrome classification is not required.....	93
Civil — Land.....	84
Civil — Water.....	85
Emergency aerodrome or aerodrome with no facilities.....	90
Heliport.....	94
Joint civil and military — Land.....	88
Joint civil and military — Water.....	89
Military — Land.....	86
Military — Water.....	87
Runway pattern in lieu of the aerodrome symbol.....	95
Sheltered anchorage.....	92
<i>Aerodrome data in abbreviated form which may be in association with aerodrome symbols.....</i>	<i>96</i>
<i>Aerodrome symbols for Approach Charts (97 and 98)</i>	
Aerodromes affecting the traffic pattern on the aerodrome on which the procedure is based.....	97
The aerodrome on which the procedure is based.....	98
RADIO NAVIGATION AIDS (99-110)	
Basic radio navigation aid symbol.....	99
Collocated VOR and DME radio navigation aids — VOR/DME.....	103
Collocated VOR and TACAN radio navigation aids — VORTAC.....	107
Compass rose.....	110
Distance measuring equipment — DME.....	102
DME distance.....	104
Instrument landing system — ILS.....	108
Non-directional radio beacon — NDB.....	100
Radio marker beacon.....	109
UHF tactical air navigation aid — TACAN.....	106
VHF omnidirectional radio range — VOR.....	101
VOR radial.....	105
AIR TRAFFIC SERVICES (111-144)	
Advisory airspace — ADA.....	115
Advisory route — ADR.....	118
Aerodrome traffic zone — ATZ.....	112
Air defence identification zone — ADIZ.....	117
Altitudes/flight levels.....	125

	<i>Symbol No</i>
ATS/MET reporting point — MRP	123
Change-over point — COP	122
Control area, Airway, Controlled route	113
Control zone — CTR	116
Final approach fix — FAF	124
Flight information region — FIR	111
Reporting and Fly-by/Flyover functionality	121
Scale-break (on ATS route)	120
Uncontrolled route	114
Visual flight path	119
<i>Airspace Classifications (126 and 127)</i>	
Aeronautical data in abbreviated form to be used in association with airspace classification symbols ..	127
Airspace classifications	126
<i>Airspace Restrictions (128 and 129)</i>	
International boundary closed to passage of aircraft except through air corridor	129
Restricted airspace (prohibited, restricted or danger area)	128
<i>Obstacles (130–136)</i>	
Elevation of top/Height above specified datum	136
Exceptionally high obstacle — lighted (optional symbol)	135
Exceptionally high obstacle (optional symbol)	134
Group obstacles	132
Lighted group obstacles	133
Lighted obstacle	131
Obstacle	130
<i>Miscellaneous (137–141)</i>	
Isogonic line or isogonal	138
Ocean station vessel (normal position)	139
Prominent transmission line	137
Wind turbine — unlighted and lighted	140
Wind turbines — minor group and group in major area, lighted	141
<i>Visual Aids (142–144)</i>	
Aeronautical ground light	143
Lightship	144
Marine light	142
SYMBOLS FOR AERODROME/HELIPORT CHARTS (145–161)	
Aerodrome reference point	151
Hard surface runway	145
Helicopter alighting area on an aerodrome	150
Hot spot	161
Intermediate holding position	160
Landing direction indicator (lighted)	156
Landing direction indicator (unlighted)	157
Obstacle light	155

	Symbol No
Pierced steel plank or steel mesh runway	146
Point light	154
Runway-holding position	159
Runway visual range (RVR) observation site	153
Stop bar	158
Stopway	148
Taxiways and parking areas	149
Unpaved runway	147
VOR check-point	152
SYMBOLS FOR AERODROME OBSTACLE CHARTS — TYPE A, B AND C (162-170)	
Building or large structure	164
Clearway	170
Escarpment	168
Pole, tower, spire, antenna, etc	163
Railroad	165
Stopway	169
Terrain penetrating obstacle plane	167
Transmission line or overhead cable	166
Tree or shrub	162
ADDITIONAL SYMBOLS FOR USE ON PAPER AND ELECTRONIC CHARTS (171-180)	
Collocated DME fix and marker beacon	180
Collocated radio navigation aid and marker beacon	178
DME fix	179
Holding pattern	173
Minimum sector altitude	171
Missed approach track	174
Radio marker beacon	177
Radio navigation aid	176
Runway	175
Terminal arrival altitude	172

2. ALPHABETICAL INDEX

	<i>Symbol No.</i>
A	
Abandoned canal	30
Advisory airspace — ADA	115
Advisory route — ADR	118
Aerodrome data in abbreviated form	96
Aerodrome Heliport Charts	145-161
Aerodrome Obstacle Charts	162-170
Aerodrome reference point	151
Aerodromes	84-98
Abandoned or closed aerodrome	91
Emergency aerodrome or aerodrome with no facilities	90
Aerodrome symbols for Approach Charts	97, 98
Aerodrome traffic zone — ATZ	112
Aeronautical ground light	143
Air defence identification zone — ADIZ	117
Airspace, advisory — ADA	115
Airspace classifications	126, 127
Airspace (prohibited, restricted or danger area), restricted, and common boundary of two areas	128
Airspace restrictions	128, 129
Air Traffic Services	111-144
Airway — AWY	113
Altitude	
Minimum sector	171
Terminal arrival	172
Altitudes/flight levels	125
Anchorage, sheltered	92
Antenna	163
Areas	
Built-up	47-50
Not surveyed for contour information or relief data incomplete	18
Prohibited	128
Restricted	128
ATS/MET reporting point — MRP (compulsory, on request)	123
B	
Bluff	4
Boundaries	
International	63
Outer	64
Building (on Aerodrome Obstacle Charts)	164
Buildings	50

	<i>Symbol No</i>
C	
Cable, overhead	166
Canal	29
Canal, abandoned	30
Change-over point — COP	122
Charted isolated rock	44
Chart, highest elevation on	12
Chart symbols, electronic	108 143, 171-180
Church	80
City or large town	47
Clearway — CWY	170
Cliff	4
Coast guard station	73
Collocated DME fix and marker beacon	180
Collocated radio navigation aid and marker beacon	178
Collocated VOR and DME radio navigation aids — VOR/DME	103 110
Collocated VOR and TACAN radio navigation aids — VORTAC	107 110
Compass rose	110
Coniferous trees	15
Contours	1
Contours approximate	2
Control area — CTA	113
Controlled route	113
Control zone — CTR	116
Coral reefs and ledges	22
Culture	47-83
Culture, miscellaneous	63-83
D	
Dam	67
Danger area	128
Danger line	43
Distance measuring equipment — DME	102, 110, 176, 177
DME distance	104
DME fix	179
Collocated DME fix and marker beacon	180
Dry lake bed	39
Dual highway	57
Dunes, sand	6

	<i>Symbol No.</i>
E	
Electronic chart symbols	108, 143, 171-180
Elevation (of doubtful accuracy), spot	14
Elevation, spot	13
Escarpment	4
Escarpment (on Aerodrome Obstacle Charts)	168
Esker	9
F	
Falls	28
Fence	65
Ferry	68
Final approach fix — FAF	124
Flight information region — FIR	111
Flight levels	125
Forest ranger station	76
Fort	79
G	
Gas field	70
Glaciers	42
Gravel	8
H	
Hard surface runway	145
Helicopter alighting area on an aerodrome	150
Heliport	94
Highest elevation on chart	12
Highway, dual	57
Highways and roads	57-62
Holding pattern	173
Hot spot	161
Hydrography	19-46
I	
Ice caps	42
Instrument landing system — ILS	108
Intermediate holding position	160
International boundary closed to passage of aircraft except through air corridor	129
Intersection INT	121
Isogonic line or isogonal	138















	<i>Symbol No</i>
L	
Lake bed, dry	39
Lakes	
Non-perennial	32
Perennial	31
Land	
Civil	84
Military	86
Joint civil and military	88
Land features appropriately labelled, unusual	10
Landing direction indicator	
Lighted	156
Unlighted	157
Large river (perennial)	23
Large structure	164
Lava flow	5
Ledges	22
Levee	9
Lightship	144
Lookout tower	74
M	
Marine light	142
Mine	75
Minimum sector altitude — MSA	171
Miscellaneous symbols	
Air Traffic Services	137-141
Culture	63-83
Missed approach track	174
Mosque	81
Mountain pass	11
N	
NDB	121
Non-directional radio beacon — NDB	100
Nuclear power station	72
O	
Obstacle light	155
Obstacles	130-136
Ocean station vessel	139
Oil field	70
Overhead cable	166

	<i>Symbol No.</i>
P	
Pagoda	82
Palms	17
Parking areas	149
Pierced steel plank or steel mesh runway	146
Pipeline	69
Point light	154
Pole	163
Power station, nuclear	72
Primary road	58
Prohibited area	128
Prominent transmission line	137
R	
Race track	77
Radio marker beacon	109, 177
Radio navigation aid	176
Basic	99
Collocated radio navigation aid and marker beacon	178
Collocated VOR and DME	103
Collocated VOR and TACAN	107
Radio navigation aids	99-110, 176, 178
Railroad (on Aerodrome Obstacle Charts)	165
Railroads (Culture)	51-56
Rapids	27
Relief data incomplete	18
Relief shown by hachures	3
Reporting and fly-by flyover functionality	121
Reservoir	38
Restricted airspace (prohibited, restricted or danger area) and common boundary of two areas	128
Restricted area	128
Rice field	36
River	
(Perennial), small	24
(Perennial), large	23
Rivers and streams	
Non-perennial	25
Unsurveyed	26
Road bridge	61
Road, primary	58
Road, secondary	59
Roads (Highways and Roads)	57-62
Road tunnel	62
Rock awash	45
Rock, charted isolated	44

	<i>Symbol No.</i>
Route	
Advisory — ADR	118
Controlled	113
Uncontrolled	114
Ruins	78
Runway	
Hard surface	175
Unpaved	145
Runway-holding position	147
Runway visual range (RVR) observation site	159
Runway visual range (RVR) observation site	153
 S	
Salt lake	33
Salt pans (evaporator)	34
Sand area	7
Sand dunes	6
Scale-break (on ATS route)	120
Secondary road	59
Sheltered anchorage	92
Shoals	41
Shore line	
Reliable	19
Unreliable	20
Shrub	162
Small river (perennial)	24
Spire	163
Spot elevation	13
Spot elevation (of doubtful accuracy)	14
Spring (perennial or intermittent)	37
Stadium	77
Steel mesh runway	146
Steel plank, pierced	146
Stop bar	158
Stopway — SWY (on Aerodrome/Heliport Charts)	148
Stopway — SWY (on Aerodrome Obstacle Charts)	169
Streams	25, 26
Structure, large	164
Swamp	35
 T	
TACAN	121
TACAN (UHF tactical air navigation aid)	106, 110
Tank farms	71
Taxiways	149
Telegraph or telephone line (when a landmark)	66
Temple	83

	<i>Symbol No</i>
Terminal arrival altitude — TAA.....	172
Terrain penetrating obstacle plane.....	167
Tidal flats.....	21
Topography.....	1-18
Tower	
Lookout.....	74
On Aerodrome Obstacle Charts.....	163
Town.....	48
Town, large.....	47
Trail.....	60
Transmission line	
On Aerodrome Obstacle Charts.....	166
Prominent.....	137
Tree	
Coniferous.....	15
On Aerodrome Obstacle Charts.....	162
Other.....	16
U	
UHF tactical air navigation aid — TACAN.....	106, 110
Uncontrolled route.....	114
Unpaved runway.....	147
Unusual land features appropriately labelled.....	10
Unusual water features appropriately labelled.....	46
V	
VFR reporting point.....	121
VHF omnidirectional radio range — VOR.....	101, 110
Village.....	49
Visual aids.....	142-144
Visual flight path.....	119
VOR.....	121
VOR check-point.....	152
VOR/DME.....	121
VOR/DME (collocated VOR and DME radio navigation aids).....	103
VOR radial.....	105
VORTAC.....	121
VORTAC (collocated VOR and TACAN radio navigation aids).....	107
VOR (VHF omnidirectional radio range).....	101

	Symbol No.
W	
Wash	40
Water	
Civil	85
Military	87
Joint civil and military	89
Water features appropriately labelled, unusual	46
Water hole (perennial or intermittent)	37
Waypoint — WPT	121
Well (perennial or intermittent)	37
Wind turbine, unlighted and lighted	140
Wind turbines, minor group and group in major area, lighted	141

TOPOGRAPHY				
1	Contours			
2	Approximate contours			
3	Relief shown by hachures			
4	Bluff, cliff or escarpment			
5	Lava flow			
6	Sand dunes			
7	Sand area			
8	Gravel			
9	Levee or eskar			
10	Unusual land features appropriately labelled			
11	Mountain pass			
12	Highest elevation on chart	<table border="1" style="border-collapse: collapse;"> <tr> <td style="text-align: center;">17456</td> </tr> <tr> <td style="text-align: center;">Alternative 17456</td> </tr> </table>	17456	Alternative 17456
17456				
Alternative 17456				
13	Spot elevation	<table border="1" style="border-collapse: collapse;"> <tr> <td style="text-align: center;">.0097</td> </tr> <tr> <td style="text-align: center;">.0075</td> </tr> </table>	.0097	.0075
.0097				
.0075				
14	Spot elevation (of doubtful accuracy)	.0370		
15	Coniferous trees			
16	Other trees			
17	Palms			
18	Areas not surveyed for contour information or relief data incomplete			
	Caution			

CULTURE

BUILT-UP AREAS		HIGHWAYS AND ROADS		MISCELLANEOUS (Cont.)				
47	City or large town		57	Dual highway		69	Pipeline	
48	Town		58	Primary road		70	Oil or gas field	
49	Village		59	Secondary road		71	Tank farms	
50	Buildings		60	Trail		72	Nuclear power station	
RAILROADS		MISCELLANEOUS		73	Coast guard station			
51	Railroad (single track)		63	Boundaries (international)		74	Lookout tower	
52	Railroad (two or more tracks)		64	Outer boundaries		75	Mine	
53	Railroad (under construction)		65	Fence		76	Forest ranger station	
54	Railroad bridge		66	Telegraph or telephone line (when a landmark)		77	Race track or stadium	
55	Railroad tunnel		67	Dam		78	Ruins	
56	Railroad station		68	Ferry		79	Fort	
AERODROMES		AERODROMES		80	Church			
84	Civil Land		88	Joint civil and military Land		81	Mosque	
85	Civil Water		89	Joint civil and military Water		82	Pagoda	
86	Military Land		90	Emergency aerodrome or aerodrome with no facilities		83	Temple	
87	Military Water		91	Abandoned or closed aerodrome		92	Sheltered anchorage	
<p>25 Note — Where required by the function of the chart, the runway pattern of the aerodrome may be shown in lieu of the aerodrome symbol, for example:</p>		<p>93 Aerodrome for use on charts on which aerodrome classification is not required e.g. Enroute Charts</p>		<p>94 Heliport Note — Aerodrome for the exclusive use of helicopters</p>				

AERODROMES (Cont.)
AERODROME DATA IN ABBREVIATED FORM WHICH MAY BE
IN ASSOCIATION WITH AERODROME SYMBOLS
 (Reference: 16.9.2.2 and 17.9.2.2)

	Name of aerodrome	
Elevation given in the units of measurement (metres or feet) selected for use on the chart	LIVINGSTONE 337 (L) = 10	Length of longest runway in hundreds of metres or feet (whichever unit is selected for use on the chart)
Minimum lighting - obstacles, boundary of runway lights and lighted wind indicator or landing direction indicator	Note - A dash (-) is to be inserted where L or H are not apply	Runway kept surfaced, normally all weather

AERODROME SYMBOLS FOR APPROACH CHARTS

97	Aerodromes affecting the traffic pattern of the aerodrome on which the procedure is based		98	The aerodromes on which the procedure is based	
----	---	--	----	--	--

RADIO NAVIGATION AIDS*

99	Basic radio navigation aid symbol Note - This symbol may be used with or without a box to enclose the data		107	Collocated VOR and TACAN radio navigation aids	VORTAC
100	Non-directional radio beacon	NDB	108	Instrument landing system	PLAN VIEW PROFILE Note - Marker beacon may be shown by outline, or stipple, or both
101	VHF omnidirectional radio range	VOR	109	Radio marker beacon	Elliptical Bone Shape
102	Distance measuring equipment	DME			
103	Collocated VOR and DME radio navigation aids	VOR/DME			
104	DME distance Distance in kilometres (statute miles) to DME Identification of radio navigation aid	15 km K 4 V			
105	VOR radial Radial bearing from and identification of VOR	R 090 KA V			
106	JMF tactical air navigation aid	TACAN			
110	Compass rose To be orientated on the chart in accordance with the alignment of the station (normally Magnetic North)				Compass rose to be used as appropriate in combination with the following symbols: VOR VOR/DME TACAN VORTAC
		Note - Additional points of compass may be added as required			

*Note - Guidance material on the presentation of radio navigation aid data is given in the Aeronautical Chart Manual (Doc 8697)

AIR TRAFFIC SERVICES

111	Flight information region	FR		117	Air defence identification zone	ADIZ	
112	Aerodrome traffic zone	ATZ		118	Advisory route	ADR	
113	Control area Anway Controlled route	CTA AWY		119	Visual flight path		
114	Uncontrolled route			120	Scale-break (on ATS route)		
115	Advisory airspace	ADA					
116	Control zone	CTR					

	REPORTING FLY-BY/FLY-OVER	Significant Point Depiction for Conventional Navigation		Significant Point Depiction for Area Navigation			
		On request (N/A)	Compulsory (N/A)	On request fly-by	Compulsory fly-by	On request flyover	Compulsory flyover
121 Basic Symbols with functionality	VFR reporting point						
	Intersection INT						
	VORTAC						
	TACAN						
	VOR						
	VOR/DME						
	NDB						
	Waypoint WPT	Not Used	Not Used				

122	Change-over point To be superimposed on the appropriate route symbol at right angles to the route	CCP		123	ATS/MET reporting point	MRP	Compulsory 	124	Final approach fix	FAP	
							On request 				

AIR TRAFFIC SERVICES (cont.)

125	Altitudes/flight levels	Altitude/flight level "window"	17 000 10 000	FL 220 10 000
		"At or above" altitude/flight level	7 000	FL 70
		"At or below" altitude/flight level	5 000	FL 50
		"Mandatory" altitude/flight level	1 000	FL 30
		"Recommended" procedure altitude/flight level	5 000	FL 50
		"Expected" altitude	Expect 5 000	Expect FL 50

Note — For use only on SID and STAR charts. Not intended for depiction of minimum obstacle clearance altitude.

AIRSPACE CLASSIFICATIONS

128	Airspace classifications		<p>Aeronautical data in abbreviated form to be used in association with airspace classification symbols</p> <p>127</p> <table border="1"> <tr> <td>TMA DONLON</td> <td>119.1</td> <td>C</td> <td>200m AGL - FL 245</td> </tr> <tr> <td>Type</td> <td>Name or call sign</td> <td>Radio (frequency/ies)</td> <td>Airspace classification Vertical limits</td> </tr> </table> <table border="1"> <tr> <td>TMA DONLON</td> <td>FL 245</td> <td>200m AGL</td> <td>119.1</td> </tr> <tr> <td>C</td> <td></td> <td></td> <td></td> </tr> </table>	TMA DONLON	119.1	C	200m AGL - FL 245	Type	Name or call sign	Radio (frequency/ies)	Airspace classification Vertical limits	TMA DONLON	FL 245	200m AGL	119.1	C			
		TMA DONLON		119.1	C	200m AGL - FL 245													
Type	Name or call sign	Radio (frequency/ies)	Airspace classification Vertical limits																
TMA DONLON	FL 245	200m AGL	119.1																
C																			

AIRSPACE RESTRICTIONS

128	Restricted airspace (prohibited, restricted or danger area)		Common boundary of two areas	
	Note — The angle and density of hatching may be varied according to scale and the size, shape and orientation of the area.			
129	International boundary closed to passage of aircraft except through air corridor			

OBSTACLES

130	Obstacle		134	Exceptionally high obstacle (optional symbol)	
131	Lighted obstacle		135	Exceptionally high obstacle — lighted (optional symbol)	
132	Group obstacles		Note — For obstacles having a height of the order of 300 m (1 000 ft) above terrain.		
133	Lighted group obstacles		136	Elevation of top (italics)	

MISCELLANEOUS

137	Prominent transmission line		140	Wind turbine – unlighted and lighted	
138	Isogonic line or isogonal		141	Wind turbines – minor group and group in major area, lighted	
139	Ocean station vessel (normal position)				

VISUAL AIDS

142	Marine light Note 2: Characteristics are to be indicated as follows:	<table border="0"> <tr> <td>Alt</td> <td>Alternating</td> <td>F</td> <td>Fixed</td> </tr> <tr> <td>R</td> <td>Blue</td> <td></td> <td></td> </tr> <tr> <td>F</td> <td>Fixed</td> <td></td> <td></td> </tr> </table>	Alt	Alternating	F	Fixed	R	Blue			F	Fixed			<table border="0"> <tr> <td>F</td> <td>Flashing</td> <td>Occ</td> <td>Occulting</td> <td>Sec</td> <td>Second</td> </tr> <tr> <td>G</td> <td>Green</td> <td>R</td> <td>Red</td> <td>(H)</td> <td>Unwatched</td> </tr> <tr> <td>Gr</td> <td>Group</td> <td>SFC</td> <td>Sector</td> <td>W</td> <td>White</td> </tr> </table>	F	Flashing	Occ	Occulting	Sec	Second	G	Green	R	Red	(H)	Unwatched	Gr	Group	SFC	Sector	W	White	<p>Note 1: Marine alternating lights are red and white unless otherwise indicated. Marine lights are white unless colours are stated.</p>
Alt	Alternating	F	Fixed																															
R	Blue																																	
F	Fixed																																	
F	Flashing	Occ	Occulting	Sec	Second																													
G	Green	R	Red	(H)	Unwatched																													
Gr	Group	SFC	Sector	W	White																													
143	Aeronautical ground light	<table border="0"> <tr> <td>☆</td> <td>★</td> </tr> <tr> <td></td> <td>Electronic</td> </tr> </table>	☆	★		Electronic	144	Lightship																										
☆	★																																	
	Electronic																																	

SYMBOLS FOR AERODROME/HELIPORT CHARTS

145	Hard surface runway		154	Point light					
146	Pierced steel plank or steel mesh runway		155	Obstacle light					
147	Unpaved runway		156	Landing direction indicator (lighted)					
148	Stopway SWY		157	Landing direction indicator (unlighted)					
149	Taxiways and parking areas		158	Stop bar					
150	Helicopter sighting area on an aerodrome		159	Runway-holding position Note: For application, see Annex 14, volume 1, 3.2.10.	<table border="0"> <tr> <td>Pattern A</td> <td></td> </tr> <tr> <td>Pattern B</td> <td></td> </tr> </table>	Pattern A		Pattern B	
Pattern A									
Pattern B									
151	Aerodrome reference point ARP		160	Intermediate holding position Note: For application, see Annex 14, volume 1, 3.2.11.					
152	VOR check point		161	Hot spot Note: Hot spot location to be circled.					
153	Runway visual range (RVR) observation site								

SYMBOLS FOR AERODROME OBSTACLE CHARTS - TYPE A, B AND C

	Plan	Profile		Plan	Profile	
162	Tree or shrub		Identification number	167	Terrain penetrating obstacle plane	
163	Pole, tower, spire, antenna, etc.			168	Escarpment	
164	Building or large structure		Identification number	169	Stopway SWY	
165	Railroad			170	Cleanway CWY	
166	Transmission line or overhead cable					

ADDITIONAL SYMBOLS FOR USE ON PAPER AND ELECTRONIC CHARTS

PLAN VIEW		Electronic
171	<p>Minimum sector altitude</p> <p>Note — This symbol may be modified to reflect particular sector shapes</p>	MSA
172	<p>Terminal arrival altitude</p> <p>Note — This symbol may be modified to reflect particular TAA shapes</p>	TAA
173	Holding pattern	
174	Mixed approach track	
PROFILE		
175	Runway	
176	Radio navigation aid (type of aid and its use in the procedure to be annotated on top of the symbol)	
177	Radio marker beacon (type of beacon to be annotated on top of the symbol)	
178	Collocated radio navigation aid and marker beacon (type of aid to be annotated on top of the symbol)	
179	DME fix (distance from DME and the fix use in the procedure to be annotated on top of the symbol)	
180	Collocated DME fix and marker beacon (distance from DME and the type of beacon to be annotated on top of the symbol)	

THIRD SCHEDULE
COLOUR GUIDE

CHART SYMBOLS




























<p>Culture, except highways and roads, outlines of large cities, grids and graticules, spot elevations, danger lines and off-shore rocks, names and lettering except for aeronautical and hydrographic features</p>	<p>BLACK</p>	
<p>Built-up areas of cities</p>	<p>BLACK Stipple</p>	
<p>Highways and roads</p>	<p>Optional colours</p>	
<p>Built-up areas for cities (alternative to black stipple)</p>	<p>RED</p>	
<p>Built-up areas for cities (alternative to black stipple)</p>	<p>YELLOW</p>	
<p>Contours and topographic features: Items 1 through 19 of Appendix 2 Hydrographic features: Items 39 through 41 of Appendix 2</p>	<p>BROWN</p>	
<p>Shore lines, drainage, rivers, lakes, bathymetric contours and other hydrographic features including their names or description</p>	<p>BLUE</p>	
<p>Open water areas</p>	<p>BLUE Half-tone</p>	
<p>Salt lakes and salt pans</p>	<p>BLUE Stipple</p>	
<p>Large non-perennial rivers and non-perennial lakes</p>	<p>BLUE Stipple</p>	
<p>Aeronautical data, except for Enroute and Area Charts — ICAO, where different colours may be required. Both contours may be used on the same sheet but, where only one colour is used, dark blue is preferred.</p>	<p>Optional colours</p>	
<p>Aeronautical data, except for Enroute and Area Charts — ICAO, where different colours may be required. Both contours may be used on the same sheet but, where only one colour is used, dark blue is preferred.</p>	<p>DARK BLUE</p>	

CHART SYMBOLS (Cont.)


<p>Woods</p>	<p>GREEN</p> 
<p>Areas which have not been surveyed for contour information or relief data are incomplete</p>	<p>Optional colours</p> <p>GOLDEN BUFF</p> 
	<p>WHITE</p> 

HYSOMETRIC TINTS

	<p>WHITE</p> <p>Tint for extreme elevations</p>	<p>SEPIA</p> 
	<p>VIOLET</p>	
	<p>ORANGE or BUFF</p> <p>Tint for higher range elevations</p>	<p>BROWN</p> 
	<p>YELLOW</p> <p>Tint for middle range elevations</p>	<p>BUFF</p> 
	<p>GREEN</p> <p>Tint for lower range elevations</p>	<p>Optional colours</p> <p>GREEN</p> 
	<p>BLUE GREEN</p> <p>Tint for areas below sea level</p>	<p>Optional colours</p> <p>WHITE</p> 
		<p>BLUE GREEN</p> 
		<p>LIGHT GREY</p> 

Note — Basic tints are identical to those specified for the International Map of the World


FOURTH SCHEDULE
HYPOSOMETRIC TINT GUIDE



Note 1 -- These tints are identical to those specified for the International Map of the World

Note 2 -- Elevations have not been associated with tints of either system in order to allow for flexibility in their selection

FIFTH SCHEDULE
SHEET LAYOUT FOR THE WORLD AERONAUTICAL CHART ICAO 1:1,000,000



SIXTH SCHEDULE
AERONAUTICAL DATA QUALITY REQUIREMENTS

Table 1 Latitude and Longitude

<i>Latitude and Longitude</i>	<i>Chart Resolution</i>	<i>Integrity Classification</i>
Flight information region boundary points.	as plotted	routine
P, R, D area boundary points (outside CTA/CTZ boundaries).	as plotted	routine
P, R, D area boundary points (inside CTA/CTZ boundaries).	as plotted	essential
CTA/CTZ boundary points.	as plotted	essential
En-route NAV/AIDS and fixes, holding STAR/SID points.	1sec	essential
Obstacles in Area 1 (the entire State territory).	as plotted	routine
Aerodrome/ heliport reference point.	1 sec	routine
NAVAIDS located at the aerodrome/heliport.	as plotted	essential
Obstacles in Area 3.	1/10sec	essential

<i>Latitude and Longitude</i>	<i>Chart Resolution</i>	<i>Integrity Classification</i>
Obstacles in Area 2.	1/10sec	essential
Final approach fixes/points and other essential fixes/points comprising the instrument procedure.	1 sec	essential
Runway thresholds	1 sec	critical
Taxiway centre line/parking guidance line points	1/100 sec	essential
Runway end (flight path alignment point)	1 sec	critical
Runway holding position.	1 sec	critical
Taxiway intersection marking line.	1 sec	essential
Exit guidance line.	1 sec	essential
Apron boundaries (polygon)	1 sec	routine
Aircraft stand points/INS checkpoints.	1/100 sec	routine
Geometric centre of TLOF or Final approach and take-off area thresholds, heliports.	1 sec	critical

Table 2 Elevation/ Altitude/ Height

<i>Elevation/Altitude/Height</i>	<i>Chart Resolution</i>	<i>Integrity Classification</i>
Aerodrome/heliport elevation	1m or 1ft	essential
World Geodetic System 84 geoid undulation at aerodrome/heliport elevation position.	1m or 1ft	essential
Runway or Final approach and take-off area threshold, non-precision approaches.	1m or 1ft	essential
World Geodetic System -84 geoid undulation at runway or Final approach and take-off area threshold, TLOF geometric centre, non-precision approaches	1m or 1ft	essential
Runway or Final approach and take-off area threshold, precision approaches.	0.5m or 1ft	critical
World Geodetic System -84 geoid undulation at runway or Final approach and take-off area threshold, TLOF geometric centre, precision approaches	0.5m or 1ft	critical
Threshold crossing height (Reference datum height) precision approaches	0.5m or 1ft	critical
Obstacle clearance altitude/height	As specified in	essential

<i>Elevation/Altitude/Height</i>	<i>Chart Resolution</i>	<i>Integrity Classification</i>
	(Doc 8168)	
Obstacles in Area 1 (the entire state territory).	3m (10 ft)	routine
Obstacles in Area 2.	1m or 1ft	essential
Obstacles in Area 3.	1m or 1ft	essential
Distance measuring Equipment	30m (100ft)	essential
Instrument approach procedures altitude	As specified in	essential
	(Doc 8168)	
Minimum altitudes	50m or 100ft	Routine
Heliport crossing height, PinS approaches	1m or 1ft	essential

Table 3 Gradients and Angles

<i>Type of gradient/angle</i>	<i>Chart resolution</i>	<i>Integrity Classification</i>
Non-precision final approach descent gradient	0.1 per cent	critical
Final approach descent angle (Non-precision approach or approach with vertical guidance).	0.1 degree	critical
Precision approach glide path/elevation angle	0.1 degree	critical

Table 4 Magnetic Variation

<i>Magnetic variation Chart</i>	<i>Chart resolution</i>	<i>Integrity Classification</i>
Aerodrome/heliport magnetic variation	1 Degree	essential

Table 5 Bearing

<i>Bearing</i>	<i>Publication Resolution</i>	<i>Integrity Classification</i>
Airway segments.	1 degree	routine
Bearings used for the formation of an en route and of a terminal fix	1/10 degree	routine
Terminal arrival/departure route segment	1 degree	routine
Bearings used for the formation of an instrument approach procedure fix	1/10 degree	essential
ILS localizer alignment	1 degree	essential
MLS zero azimuth alignment	1 degree	essential
Runway and Final approach and take-off area bearing	1 degree	routine

Table 6 Length / Distance / Dimension

<i>Length/distance/dimension</i>	<i>Chart resolution</i>	<i>Integrity Classification</i>
Airway segment length	1 km or 1 NM	routine
Distance used for the formation of an en route fix	2/10 km (1/10 NM)	routine
Terminal arrival/departure route segment length	1 km or 1 NM	essential
Distance used for the formation of a terminal and instrument approach procedure fix	2/10 km (1/10 NM)	essential
Runway and Final approach and take-off area length, TLOF dimensions	1m	critical
Runway width	1m	essential
Stop way length and width	1m	critical
Landing distance available	1m	critical
Take-off run available	1m	critical
Take-off distance available	1m	critical
Accelerate-stop distance available	1m	critical
ILS localizer antenna-runway end, distance	As plotted	routine
ILS glide slope antenna-threshold, distance along centre line	As plotted	routine
ILS marker-threshold distance	2/10 km (1/10 NM)	essential
ILS DME antenna-threshold, distance along	as plotted	essential

<i>Length/distance/dimension</i>	<i>Chart resolution</i>	<i>Integrity Classification</i>
centre line 1×10^{-5} / essential		
MLS azimuth antenna-runway end, distance 1×10^{-3} / routine	as plotted	routine
MLS elevation antenna-threshold, distance along centre line	as plotted	routine
MLS DME/P antenna-threshold, distance along centre line	as plotted	essential

Made on the 18th June, 2018.

JAMES MACHARIA,
Cabinet Secretary,
Ministry of Transport, Infrastructure, Housing and Urban Development.

